



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation 350v3 Friction Feeder



At a Glance

- Maximum product width: 11.8in (300mm)
- Low-cost low-demand feeder
- Transports medium-sized to very large carton blanks, flat sheets and other base products quickly and efficiently

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Accurate Feeding of Common Products at a Lower Price

The MFT Automation v3 Signature Series are economical, cost-effective friction feeders. Designed and built with the same quality as the premium ip feeders, the v3 Signature Series is engineered for lower throughput applications. With a powerful 500-watt two-thirds horsepower brushless servo motor, computer controls, and four different discharge lengths available makes the Signature Series friction feeder a top contender in its class.

The Signature Series feeders are a strong, robust and reliable lower-demand machines for simpler applications providing dependability on the production floor.

The Multifeeder 350v3 friction feeder feeds all the same products as the 350ip3 feeders up to 300mm (11.8") wide products, providing more width for common and somewhat larger product feeding. Like the 350ip3 feeder, larger working area over the discharge for added accessories is ideal for tipping, affixing and labeling with other product systems.

When large and medium-sized products are needed to feed and high speed is not essential, combined with cost savings and reliability, the 350v3 friction feeder machine is your best choice.

Features

Mechanical design is modular for many custom configurations

Simplified control interface software package ensures flexible and precise control

Infrared sensor for accurate count. Upgradeable to double-detect and overlap detection

Single-sided controls provide for efficient operation

Performance designed for long production runs
Patented feed separating mechanism
Closed loop system with encoder feedback

Products

Feeds all the same products as the 250v3
Medium and small size cartons
Copy or carbon paper
Spiral notebooks
Larger pouches or clear bags
Bundled product wraps
Magazines
Large dividers
Envelopes
Cardboard easels
Calendars
X-Ray film
Folded bags
Zippered bags
Folders
Shooting targets
Mail packs
Medical pouches
Large sheets or cardstock
And much more

Product Specs

Width: 1.96" (50mm) - 11.81" (300mm)
Length: 1.96" (50mm) - 12.8" (325mm)
Thickness: 0.003" (0.075 mm) - 1.0" (25mm)

Industries

Pharmaceutical
Cosmetics
Financial
Robotics
Food
Packaging
Printing

Typical Applications

Tipping or affixing (optional upgrade)
Batch count (optional upgrade)
Collating
Labeling
Printing, inspecting and rejecting
Integrating an Automatic Product Loader (APL)

Integrated as a base feeder to another application
Standard performance level only

Integration Equipment

Conveyers
Poly baggers
Order fulfillment
Collators
Shrink wrappers
Folder / gluer
Case-packers
Banders
Existing bases
Flow wrappers
Cartoners

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

MFT 350v3 Machine Specifications

Typical Height	31.7" (856mm)
Typical Length (ED)	25.4" (645mm)
Typical Width	25.1" (637mm)
Maximum Belt Speed	140 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	50-95F (10-35C)
Weight Ranges	75-125 lbs
Operating Humidity	30-90%

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.