



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# MFT Automation 550ip3 HCP Friction Feeder

## At a Glance

- 500 millimeter width capability
- Tipping at speeds up to 200 mpm
- Modular mechanical design for custom configurations
- Robust brushless servo motor for tight precise placement

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



## Faster Speeds, Tighter Placement, 500mm Width Capability

The MFT Automation High Continuous Performance (HCP) friction feeder expands on the performance and accuracy already built into the Multifeder Industrial Performance (ip) Series friction feeders.

The HCP feeder unifies high-performance parts with specially tuned software. This high continuous performance feeding machine will allow you to take your production to the next level of productivity. High linear speeds and tighter placement equate to more product throughput.

## Features

Modular mechanical design for custom configurations, robust brushless servo motor for tight precise placement.

Can feed very large products.

Premium high strength hard carcass belts with minimal stretch for longer life and long production runs.

Easy to use updated MFT proprietary ip3 software package ensures flexible and precise control.

Updated Accutipping algorithms for speed and accuracy.

Improved infrared sensor detects a wider range of products for accurate count, double-detect, and overlap detection.

Patented MFT feed separating mechanism.

Closed loop system with encoder feedback.

## Applications

Accurate high-speed tipping and affixing

Feed into a box, into a pocket on a conveyor, onto a catch tray, or other secondary operation

Batching, collating systems and barcode / vision systems

Poly baggers  
Case packers  
Cartoners  
Order fulfillment  
Collators  
Banders

## Products

Bags  
Pouches  
Pamphlets  
Card stock  
Gift cards  
Coupons  
Magnets  
Bandages  
Carton blanks  
Tyvek sheets  
Pharma inserts

## Product Specs

Width: 1" (25mm) - 19.6" (500mm)  
Length: 1.57" (40mm) - 19.6" (500mm)  
Thickness: 0.003" (0.075 mm) - 1" (25mm)

## Industries

Pharmaceutical  
Food  
Cosmetics  
Contract packaging  
Financial  
Printing  
Robotics

## Integration Equipment

Imaging lines  
Conveyers  
Shrink wrappers  
Folder / gluer  
Existing bases  
Flow wrappers

## Options

Open discharge  
Integrated printing, camera, scoring  
Accutipping

## Specifications

Typical Height	36.1" (918mm)
Typical Length	25.5" (648mm)
Typical Width	32.9" (837mm)
Maximum Speed	200 meters per minute
Power	110/220V 50-60Hz 6A
Operating Temp	50° - 95°F (10° - 35°C)
Weight Range	75 - 125 lbs
Operating Humidity	30 - 90

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.