



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation MFT 550v3 Friction Feeder



At a Glance

- Maximum product width: 500mm (19.6in)
- Low-cost low-demand feeder
- Transports medium-sized to very large carton blanks, flat sheets and other base products quickly and efficiently

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Low-Cost Wide-Body Feeder for Large Products

The Multifeeders v3 Signature Series are economical, cost-effective friction feeders. Designed and built with the same quality as the premium ip feeders, the v3 Signature Series is engineered for lower throughput applications. With a powerful 500-watt two-thirds horsepower brushless servo motor, computer controls, and four different discharge lengths available makes the Signature Series friction feeder a top contender in its class.

The Signature Series feeders are a strong, robust and reliable lower-demand machines for simpler applications providing dependability on the production floor.

The economical wide-body 550v3 friction feeder transports large and medium-sized irregular carton blanks, flat sheets or other base products quickly and efficiently to other applications.

The 550v3 friction feeder is designed and built with larger over-sized shafts for long production runs. Tipping and affixing of large products are ideal for the 550v3.

When large and medium-sized products are needed to feed and high speed is not essential, combined with cost savings and reliability, the 550v3 friction feeder machine is your best choice.

MFT 550v3 Typically-Fed Products

Feeds all the same products as the 250v3 and 350v3
Very large/large/medium size flat corrugated cartons
Posters
Slip sheet dividers
Large signs

Newspapers
Metal gaskets
Large pouch bags
And much more

Typical Applications

Tipping or affixing (optional upgrade)
Batch count (optional upgrade)
Collating
Labeling
Printing, inspecting and rejecting
Integrating an Automatic Product Loader (APL)
Integrated as a base feeder to another application
Standard performance level only

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

MFT 550v3 Machine Specifications

Typical Height	856mm (31.7")
Typical Length (ED)	645mm (25.4")
Typical Width	837mm (32.9")
Maximum Belt Speed	140 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	10-35C (50-95F)
Weight Ranges	75-125 lbs
Operating Humidity	30-90%

MFT 550v3 Product Specifications

Minimum Size	50mmW x 50mmL (1.96"W x 1.96"L)
Maximum Size	500mmW x 325mmL (19.68W" x 12.79"L)
Minimum Thickness	0.075mm (.003")
Maximum Thickness	25mm