



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# MFT Automation Hygienic Washdown Friction Feeder 600



## At a Glance

- Type 304 series stainless steel
- Complies with IP66 or higher and NEMA4X standards
- Moisture and corrosion resistant meets FDA standards
- Self-draining, easy cleaning and maintenance
- Maximum product size 23.6in W x 12.79in L

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Fast, Accurate Hygienic Feeding of Wide Food Packaging

The MFT Automation Hygienic Washdown Friction Feeder 600 meets sanitary requirements and complies with IP66 or higher as well as NEMA4X standards.

The Hygienic Friction Feeder 600 is designed for the food industry that must repetitively and aggressively clean their production floor equipment. This clean in place (CIP) friction feeder is engineered with type 304 stainless steel, powered by a 1200 watt brushless servo motor, and is moisture and corrosion resistant and meets FDA standards.

The open design of this hygienic feeder has minimal disassembly for easy cleaning and maintenance. This feeder is self-draining, and has compatible materials with no hollow areas to ensure the sanitary design and reduced risk of contamination.

## Features

Engineered with type 304 stainless steel and passivated for corrosion resistance.

Constructed with minimal contamination points.

Open design allows for minimal disassembly with easy cleaning and maintenance, reducing risk of contamination.

Computer-controlled brushless servo motor technology prevents production interruptions for precise product placement.

Highly-adaptable software package with optional upgrades.

Resistance to moisture and corrosion, equivalent to NEMA rated 4X enclosures.

FDA compliant feed belts are available for food grade applications.

Can meet various sanitary level requirements.  
Easy and versatile to interface using standard industry-compliant cables.

## Applications

Insertion into a catch-tray, box or conveyor  
Deliver a product to a secondary application  
Batching, high-speed tipping or affixing, collating systems and barcode/vision systems

## Products

Pizza top sheet and cardboard  
Wax slip sheets for pizzas, meat, dairy/cheese, tortillas, bakery items  
Cooking bottom tray  
Nutritional top sheet onto meat trays  
Cardboard cooking trays  
Pocket sleeves  
Meat soaker pads  
Coupons/promo labels  
Feeding vertical fill and seal bags  
Feeding cardboard for tray packing  
Blood test strips  
Petri test strips

## Product Specs

Width: 1.0" (25mm) - 23.6" (600mm)  
Length: 1.57" (40mm) - 12.8" (325mm)  
Thickness: 0.003" (0.075 mm) - 1.0" (25mm)

## Industries

Pharmaceutical  
Food  
Clean room environments

## Integration Equipment

Shrink wrappers  
Existing bases  
Conveyers  
Flow wrappers  
Baggers  
Case packers  
Collators  
Cartoners  
Banders

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

# Specifications

|                      |                       |
|----------------------|-----------------------|
| Typical Height       | 39.7" (1008mm)        |
| Typical Length (XED) | 37.1" (943mm)         |
| Typical Width        | 41.1" (1045mm)        |
| Maximum Belt Speed   | 140 meters per minute |
| Power Requirements   | 110/220V 50-60Hz 6amp |
| Operating Temp       | (35-95F) (2-35C)      |
| Weight Ranges        | Approx 400 lbs        |
| Operating Humidity   | 30-100%               |

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.