



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation VTC Vacuum Track Conveyor System

At a Glance

- Firmly controls product after it exits feeder
- Provides control of irregular products
- Standard 2 and 4 meter lengths, with other lengths available

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



High-Performance Conveying System Firmly Secures Product

The MFT Automation VTC conveying system can be one solid belt or configured in individual belt tracks to meet your specific conveying application.

The MFT Automation VTC is powered by a 750 watt brushless servo motor for precise product placement. Optional upgrades to 1000 watts are available.

Features

Designed to firmly control product after it exits the feeder in order to execute secondary operations. Provide better control of irregular product by spreading out product on a flat horizontal conveyor. Standard 2 and 4 meter lengths. Other lengths available. Linear mounting bars provide quick mounting of optional components, such as inkjet or laser coders, scanners, vision systems and more.

Applications

Transport, bar-coding applications, and UPC over labeling.
DVD, Blu-ray, and lenticular affixing.
Integration with feeders and more.

Products

Bags
Pouches

Pamphlets
Card stock products
Gift cards
Clear-film plastics
Magnets
Bandages
Carton blanks
Tyvek sheets
Pharma inserts

Product Specs

Width: 1.0" (25mm) - 11.81" (300mm)
Length: 1.0" (25mm) - 12.8" (325mm)
Thickness: 0.003" (0.075 mm) - 1.0" (25mm)

Industries

Pharmaceutical
Food
Cosmetics
Contract packaging
Financial
Printing
Robotics

Integration Equipment

Imaging lines
Shrink wrappers
Existing bases
Conveyers
Folder / gluer
Flow wrappers
Baggers
Case packers
Collators
Order fulfillment
Cartoners
Banders

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

Specifications

Typical Height	38.5" (978mm)
Typical Length (ED)	81.9" (2080mm)
Typical Width	25.8" (656mm)
Maximum Belt Speed	140 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	50-95F (10-35C)
Weight Ranges	75-125 lbs
Operating Humidity	30-90%

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.