



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation Hygienic Washdown Labeler 300



At a Glance

- Designed for food and medical grade applications
- Hygienic washdown labeler control panel
- Brushless servo motor for accurate label placement
- Built with 304 stainless steel

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

304 Stainless Steel with Simple Cleaning and Maintenance

The Multifeeder Washdown Labeler 300 is a robust labeler, engineered with type 304 stainless steel and passivated for corrosion resistance. This labeler's Clean-in-Place design provides minimal contamination points. This allows for minimal disassembly with easy cleaning and maintenance, therefore reducing your risk of contamination.

Brushless Servo Motors for Flexible High-Speed Accuracy

Other features of the MFT Hygienic Labeler include the computer-controlled brushless servo motors for flexible high-speed accuracy, precisely placing labels on your product. The electronic components of the labeler are self-contained, allowing for a simple elegant design. With a highly flexible proprietary software package, there are optional upgrades for the customer.

IP69K Hygienic Washdown Labeler

The Hygienic Labeler 300 meets IP69K requirements and meets and exceeds IP66/NEMA4X standards to ensure consistent washdown performance. The labeler is capable of running up to 12 inch wide labels. The adjustable angular peel plate is suitable for a wide range of applications. Separate unwind, drive, and rewind servo controls provide maximum control, stability and performance.

The MFT Hygienic Washdown Labeler 300 is available for food grade applications such as pizza, bakery, meat, clean rooms, medical, and pharmaceutical. The Hygienic Labeler can meet various sanitary level requirements depending on your application needs.

The MFT Hygienic Labeler 300 is easy to use with versatile interface using standard industry compliant

cables. The Labeler utilizes a small footprint and is easily mobile to quickly change work station locations.

Benefits

Hygienic Washdown Labeler Control Panel

Equipped with customizable computer controls with on-board panel for flexible controls. Enclosure and control buttons are designed to be hygienically sealed for IP69K, and meets and exceeds IP66/NEMA4X.

Durable Steel Shafts for Strength

Stainless steel shafts and sealed bearings will provide maximum life expectancy. Adjustable angular peel plate for a wide range of applications.

Hygienic Washdown Labeler Remote Panel

Remote control panel for easy control from the loading / operator side. Includes E-Stop button for emergency stops to safely disconnect power source.

Brushless Servo Motor for Accurate Placement

A standard 500 to 1000 watt brushless servo motor per axis depending on application is available for repeatable accuracy.

Hygienic Applications

Food and beverage labeling

Bottle Labeling

Pizza labeling

Bakery

Meat packaging

And many more

Label Specs

Width: 0.39" (10mm) - 11.96" (304mm)

Length: 0.39" (10mm) - 39.37" (1000mm)

Industries

Pharmaceutical

Food

Pizza manufacturing

Baking

Clean room environments

Meat packaging

Options

Stand-alone hygienic labeler unit with no stand

Stack light

Low label detect

Encoder with speed following accutipping

Please [contact Pro Pac](#) or call 888-318-0083 for your labeling equipment.

Specifications

Typical Height	36.1" (918mm)
Typical Length	25.5" (648mm)
Typical Width	21.1" (537mm)
Maximum Speed	125 meters per minute
Power	110/220V 50-60Hz 6A
Operating Temp	0° - 95°F (0° - 35°C)
Weight Range	400-1000 lbs
Labeler without Stand	400 lbs
Labeler with Stand	600 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your labeling equipment.