



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation Impresso Labeler



At a Glance

- Independently powered 1000 watt brushless servo motor for unwind and rewind
- Up to 20 inch diameter rolls of labels
- Multiple sensor triggers achieve accurate label placement at high speeds

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact High-Performance Label Applicator

With a small footprint and ease of mobility, the MFT Automation Impresso can fit into the tightest of production areas. This compact label feeder machine offers customizable computer controls with an on-board panel for accurate placement, a 1000-watt brushless servo motor, and durable stainless steel shafts to provide maximum life expectancy.

Features

Equipped with an independently powered 1000 watt brushless servo motor for unwind and rewind. Designed for flexibility to stand alone or integrate with existing production lines.

Highly adaptable software package can integrate multiple sensor triggers to achieve accurate label placement at high speeds.

Small compact design is versatile to handle up to 20" diameter rolls of labels.

Typical Applications

Extended content labeling
Pharmaceutical labeling
Direct mail tabbing
Food and beverage labeling
Gap-less magnet application
Gift card application
And many more

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

Impresso Machine Specifications

Typical Height	942mm (37.1")
Typical Length	1106mm (43.6")
Typical Width	370mm (14.6")
Maximum Speed	70 meters per minute
Power Requirements	110/220V, 50-60Hz, 6amp
Operating Temp	10-35C (50-95F)
Weight Ranges	Less than 80 lbs