



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Videojet 210 Label Applicator



At a Glance

- Microprocessor-controlled labeler applies pre-printed labels
- Storage of multiple production settings
- Web speed up to 98 feet per minute (30 m/min)

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Industrial Label Application

The Videojet Labeljet 210 microprocessor-controlled labeler applies pre-printed labels to a wide variety of products in low to medium-duty production environments.

The Videojet Labeljet 210 integral stepper motor drives the label web at up to 98 feet per minute (30 m/min). A shaft encoder input (for speed compensation) is standard. Optional application methods include tamp and blow modules.

Benefits

- Fast and accurate
- Simple operation
- Low maintenance
- High speed
- Microprocessor control
- Stepper motor
- Storage of multiple production settings

Options

- Mounting stand
- Product detector
- Blow module
- Shaft encoder

Alarm stack
Tamp module

Specifications

Label size	Min 0.5"W 0.5"L (12 mm x 12 mm) Max: 4.0"W x 19.7"L (104 mm x 500 mm)
Direction	left or right-hand
Accuracy	Better than ± 0.04 " (1mm)
Speed range	6.6 feet to 98.4 feet/min. (2 m to 30 m/min) variable
Unwind capacity	11.8" (300 mm) diameter (15.7" / 400 mm optional)
Display	LCD display with language-independent icons
Setup Functions	Web speed Label stop Label sensitivity Product delay and coder dwell 10 memory storage locations 3" (76 mm) core diameter
Standard Inputs	Product detector Shaft encoder Dual photocell
Standard Outputs	Lamp stack Tamp/blow Alarm Hot stamp Air assist
Electrical Requirements	230 or 110 VAC 50 - 60Hz, 250VA
Weight	50.8 lbs (23 kg)
Environment	32° to 113°F (0 ° to 45°C)

Please [contact Pro Pac](#) or call 888-318-0083 for your label applying equipment.