



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Volumetric Technologies Food Grade Transfer Pumps



At a Glance

- Designed for a variety of automatic and semi-auto operations
- Available with lobe pumps, bi-wing rotor pumps, sine pumps, and peristaltic pumps
- Handle thick or thin products, with or without solids, hot fill or cold fill

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Highly Versatile Filler / Depositor for a Variety of Products

Volumetric Technologies designs and manufactures high-quality food safe pumps to meet a wide variety of needs.

Volumetric Technologies food grade transfer pumps are constructed of USDA approved materials to gently transfer flowable products to filling, depositing, or processing line.

Volumetric Technologies food grade transfer pumps are designed to handle thick or thin products, hot or cold products, and products with or without large particulates. These food grade transfer pumps are also used for pumping products to and from cooking or holding tanks for further processing. This is all done with gentle low-shear piston pumps that reduce product degradation.

These reliable food grade transfer pumps are easy to clean. The tool-free design means you can disassemble and reassemble in just minutes.

Features

Gentle on shear sensitive products

Product contact surfaces constructed from 316L stainless steel and USDA approved materials

Built to last in the toughest environments

Quick tool-free assembly and disassembly

Adjustable speed controls

Rotary actuator valve drive assembly

Options

Available in 2", 3", and 4" port sizes

Custom product tank

Agitated product tank

Heated product tank

Controlled Manually or Automatically via level control system

Custom hoses and piping to/from the pump

Specifications

Power Requirements: Air

Speed: Up to 60 gallons per minute

Particulate Size: Up to 2" diameter

Wash Down: Full wash down

Please [contact Pro Pac](#) or call 888-318-0083 for your liquid filling equipment.