



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Fanuc M-900/330F-32B Palletizing Robot



At a Glance

- Max Payload: 330 kg
- Reach: 3203 mm
- Axis: 6

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Enhanced Robotic Rigidity for Ultimate Robotic Precision

The Fanuc M-900/330F-32B long arm robot comes with a compact mechanical construction ensuring an optimal weight-payload ratio.

The large work envelope with a horizontal reach of 3203 mm and a vertical reach of 3539 mm makes this robot an ideal solution for heavy spot welding and material handling application like palletizing.

The Fanuc M-900/330F-32B robot's inherent stiffness, along with its high payload, qualify this robot for operations that demand higher levels of rigidity from the robot.

Pro Pac provides custom end-of-arm tools and configurations that seamlessly integrate with Fanuc robots and the needs of any packaging line.

Specifications

Max Payload: 330 kg

Reach: 3203 mm

Axis: 6

Features

Floor, Ceiling and Angle Mounting Efficient in confined areas, the Fanuc M-900/330F-32B robot facilitates easy access for servicing.

Increased Robotic Reach Excellent robotic solution for tasks that demand a combination of ruggedness,

extra reach, and heavy lifting.

Optional Severe Dust and Liquid Protection (SDLP) Enhanced severe dust and liquid protection package available for use in harsh environments.

Please [contact Pro Pac](#) or call 888-318-0083 for your robotic equipment.