



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Fanuc M-900iB/280L Palletizing Robot



At a Glance

- Max Payload: 280 kg
- Reach: 3103 mm
- Axis: 6

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Robotic Rigidity Meets Robotic Extended Reach

Despite its long arm, the Fanuc M-900iB/280L robot's inherent stiffness makes it ideal for operations that demand higher levels of rigidity from the robot.

Already highly versatile with 6 axis, its supporting parallel link arm makes it even more suited to accurate handling of heavy workpieces, palletizing in complete layers and heavy-duty robotic spot welding.

Pro Pac provides custom end-of-arm tools and configurations that seamlessly integrate with Fanuc robots and the needs of any packaging line.

Specifications

Max Payload: 280 kg

Reach: 3103 mm

Axis: 6

Features

Floor, Ceiling and Angle Mounting Efficient in confined areas, the Fanuc M-900/330F-32B robot facilitates easy access for servicing.

Stiff Mechanical Unit The Fanuc M-900iB/280L robot's robust construction and supporting parallel link arm are ideal for accurate handling of heavy workpieces, palletizing in complete layers and heavy-duty spot welding.

Optional Severe Dust and Liquid Protection (SDLP) Enhanced severe dust and liquid protection package available for use in harsh environments.

Please [contact Pro Pac](#) or call 888-318-0083 for your robotic equipment.