



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Fanuc M-900iB/360 Palletizing Robot



At a Glance

- Max Payload: 360 kg
- Reach: 2655 mm
- Axis: 6

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Flexible Robotic Handling, Flexible Robotic Positioning

The Fanuc M-900iB/360 robot is ideally suited to the heavier payloads involved in assembly, parts transfer and machine tending applications.

Floor and ceiling mounting options make this robot extremely flexible, with its 6 axis providing the dexterity required for fast accurate handling. Faster cycle times and higher loads are enabled through improved cooling.

Pro Pac provides custom end-of-arm tools and configurations that seamlessly integrate with Fanuc robots and the needs of any packaging line.

Specifications

Max Payload: 360 kg
Reach: 2655 mm
Axis: 6

Features

Compact, Space-Saving Design The lightweight hollow wrist design on the Fanuc M-900/330F-32B robot protects motors from heat and harsh environments and enables higher loads and duty cycles through improved cooling.

Mounting Options The Fanuc M-900/330F-32B long arm robot comes with ceiling, floor, angle and wall mounting options.

Optional Severe Dust and Liquid Protection (SDLP) Additional robot base, drive train and J1 J2 axis protection kit available to provide dust and water protection. J3 arm and wrist come with IP67 protection as standard.

Please [contact Pro Pac](#) or call 888-318-0083 for your robotic equipment.