



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Fanuc M-3iA/6S Pick-and-Place Delta Robot



At a Glance

- Max Payload: 6 kg
- Reach: 1350 mm
- Axis: 4

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

High-Speed 4-Axis Delta Robot

Fitted with powerful servomotors for high acceleration and short cycle times, this Fanuc M-3iA/6S Delta robot is ideal for high-speed picking operations. Its 4-axis and high-speed single-axis wrist provide increased dexterity, while its long reach makes this Fanuc robot ideal for picking applications across multiple conveyors.

Specifications

Max Payload: 6 kg

Reach: 1350 mm

Axis: 4

High-Speed Picking and Kitting Applications

High-Speed Single-Axis Wrist With its single-axis wrist delivering speeds of up to 4,000 degrees/second, this Fanuc M-3iA/6S Delta robot is designed for high-speed picking and kitting applications.

IP67 as Standard With IP67 protection as standard, this food-grade Fanuc robot is ideal for dirty and dusty environments that involve complete wash-downs.

Parallel Link Design Four axis with a single-axis wrist ensure maximum speed and acceleration. A unique 6-axis parallel-link design makes expanded robotization of transfer and assembly applications simple.

Please [contact Pro Pac](#) or call 888-318-0083 for your robotic equipment.