



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Matrix Pacraft TT-8A2 Pre-Made Pouching System

At a Glance

- Designed to handle larger pouches
- Max speed 50 ppm
- User-friendly protocols and controls

Buy your [stand-up pouches](#) from us, and get a discount on this Matrix pouch filling machine!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Automatically Fill Large Pre-Made Pouches

Designed for various larger pouch formats, the Matrix Pacraft TT-8A2 quickly pouches solid, granule and powder products.

This safe and sanitary pouching machine is user-friendly designed with easy wash-down protocols, intuitive operation and simple touch-screen controls.

The TT-8A2 pouching system can run up to 50 pouches per minute, handling widths from 7.08" to 12.59" (180 - 320 mm) and lengths from 5.51" to 15.74" (140 - 400 mm).

Options include a date printer, nitrogen gas flush device, pouch pick-up position, zip close device, and many more.

Features

- Rated up to 50 pouches per min
- Designed for larger pouches
- Easy cleaning, wash-down design
- Simple, intuitive operation and maintenance using touch screen controls
- Designed for safe and sanitary operation
- Safety guarding (fully enclosed)
- Small footprint

Common Applications

Snacks
Pet food
Rice & other grains
Frozen food
Granular & powder

Options

Date printer
Deflator
Tapping
Nitrogen gas flush device
Zipper close device
Zipper open device
Dust collecting device
Synchronized following funnel (DDS1)
Adjustable gripper height device (AGH)
Product in-seal detection
Stand-up pouch bottom opening device
Pouch pick-up position detection

Typical Stations

One	Pouch staging
Two	Printing
Three	Pouch opening
Four	NA
Five	Pouch filling
Six	Nitrogen flush
Seven	Heat sealing
Eight	Cooling, discharge

Specifications

Cycle Speed	Up to 50 bpm
Pouch Width	7.08" - 12.59" (180 - 320 mm)
Pouch Length	5.51" - 15.75" (140 - 400 mm)
Pouch Material	PE and various laminates
Pouch Style	Flat, stand-up and floating gusset (optional press-to-close zipper style)
Sealing	2-stage heating/cooling
Electrical	6.5 kVa
Air	0.6 MPa (72 psi), 350 - 600 NL/min (ANR)
Machine Dimensions	88.58"W x 153.54"L x 74.80"H (2250W x 3900L x 1900H mm)
Machine Weight	4630 lbs (2100 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your pouching equipment.