

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

Contact

Our Packaging Experts solutions@propac.com 888-318-0083

Matrix Pacraft TT-8DW-N Pre-Made Pouching System



At a Glance

- Duplex high-speed pouch filler
- Max speed 80 ppm
- User-friendly protocols and controls

Buy your stand-up pouches from us, and get a discount on this Matrix pouch filling machine!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

High-Speed Pouching a Variety of Dry Products

The Matrix Pacraft TT-8DW-N pre-made pouch filler/sealer is a duplex machine, offering a high-speed flexible pouch format system that can fill and seal a variety of products.

This safe and sanitary pouching machine is user-friendly designed with easy wash-down protocols, intuitive operation and simple touch-screen controls.

Features

Rated up to 80 pouches per min

Widely flexible for various pouch formats and product types

Easy cleaning, wash-down design

Simple, intuitive operation and maintenance using touch screen controls

Designed for safe and sanitary operation

Flexible pouch formats

Easy clean and wash-down style

User friendly operation

Touch screen controls

Safety guarding (fully enclosed)

Small footprint

Common Applications

Dry & frozen food

Pet food Lawn & garden Individually wrapped products

Options

Date printer

Deflator

Tapping

N2 gas flush device

Zip open-close device

Fill pause mode

Seal area cleaning

Pouch recycle

Double pouch detection

Various filling devices

Pouch Rejection

Product in-seal detection

Stand-up pouch bottom opening device

Pouch pick-up position detection

Adjustable gripper height device (AGH)

Typical Stations

One	Pouch magazine, conveyor
Two	Printing, labeling
Three	Pouch opening
Four	Pouch filling
Five	Nitrogen flush
Six	Reject
Seven	Heat sealing
Eight	Cooling, discharge

Specifications

Cycle Speed	Up to 80 bpm
Pouch Width	4.72" - 10.24" (120 - 260 mm)
Pouch Length	5.12" - 15.75" (130 - 400 mm)
Pouch Material	PE and various laminates
Pouch Style	Flat, stand-up and floating gusset (optional press-to-close zipper style)
Sealing	2-stage heating/cooling
Electrical	9.0 kVa
Air	0.6 MPa (72 psi), 900 Nl/min (ANR)
Machine Dimensions	170.87"W x 118.31"L x 86.61"H (4340W x 3005L x 2200H mm)
Machine Weight	3968 lbs (3500 kg)

Please contact Pro Pac or call 888-318-0083 for your pouching equipment.