



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Matrix Pacraft TT-8DW-N Pre-Made Pouching System

At a Glance

- Duplex high-speed pouch filler
- Max speed 80 ppm
- User-friendly protocols and controls

Buy your [stand-up pouches](#) from us, and get a discount on this Matrix pouch filling machine!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



High-Speed Pouching a Variety of Dry Products

The Matrix Pacraft TT-8DW-N pre-made pouch filler/sealer is a duplex machine, offering a high-speed flexible pouch format system that can fill and seal a variety of products.

This safe and sanitary pouching machine is user-friendly designed with easy wash-down protocols, intuitive operation and simple touch-screen controls.

Features

- Rated up to 80 pouches per min
- Widely flexible for various pouch formats and product types
- Easy cleaning, wash-down design
- Simple, intuitive operation and maintenance using touch screen controls
- Designed for safe and sanitary operation
- Flexible pouch formats
- Easy clean and wash-down style
- User friendly operation
- Touch screen controls
- Safety guarding (fully enclosed)
- Small footprint

Common Applications

Dry & frozen food

Pet food
Lawn & garden
Individually wrapped products

Options

Date printer
Deflator
Tapping
N2 gas flush device
Zip open-close device
Fill pause mode
Seal area cleaning
Pouch recycle
Double pouch detection
Various filling devices
Pouch Rejection
Product in-seal detection
Stand-up pouch bottom opening device
Pouch pick-up position detection
Adjustable gripper height device (AGH)

Typical Stations

One	Pouch magazine, conveyor
Two	Printing, labeling
Three	Pouch opening
Four	Pouch filling
Five	Nitrogen flush
Six	Reject
Seven	Heat sealing
Eight	Cooling, discharge

Specifications

Cycle Speed	Up to 80 bpm
Pouch Width	4.72" - 10.24" (120 - 260 mm)
Pouch Length	5.12" - 15.75" (130 - 400 mm)
Pouch Material	PE and various laminates
Pouch Style	Flat, stand-up and floating gusset (optional press-to-close zipper style)
Sealing	2-stage heating/cooling
Electrical	9.0 kVa
Air	0.6 MPa (72 psi), 900 NL/min (ANR)
Machine Dimensions	170.87"W x 118.31"L x 86.61"H (4340W x 3005L x 2200H mm)
Machine Weight	3968 lbs (3500 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your pouching equipment.