



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Markem-Imaje 9750 Continuous Inkjet Printer



## At a Glance

- Up to 3,000 km of cable printing
- Inks specially formulated for high contrast and perfect adhesion
- Automatic cleaning system provides clean, hassle-free start-ups

Buy your [printer ink](#) from us, and get a discount on this Markem-Imaje printer!

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Flexible, Stable Cutting Edge Inkjet Printer

The Markem-Imaje 9750 inkjet printer supports medium to heavy duty production lines, simplifies ease of use, and contributes to sustainability.

Meticulously engineered and qualified by the most modern methods, the Markem-Imaje 9750 inkjet printer's latest enhancements bring you:

- Technology leaps grounded in time-tested industrial processes for maximized uptime, reduced maintenance.
- Cutting-edge design with simplified UI and modular components for easy operation, maintenance or repair.
- Clear, customizable, traceable codes that meet customers' growing demand for supply chain visibility.

## Innovative Inkjet Printer

**Intelli'Inks** System ensures optimal coder performance and flexibility when coding different package materials.

**Intelli'Swap** Technology streamlines mechanicals down to swappable modules.

**Jet Speed Control** Technology automatically adjusts ink and printer variables to ensure drop placement, quality and code consistence. Every time.

## More Sustainable Printing

**Intelli'Swap** Modularity enables you swap out only the individual parts that need to be replaced and not the entire block.

**Intelli'Design** Process and a portfolio of rigorously developed ink formulations help reduce consumable

consumption and VOC emissions by up to 50% while improving operator safety, well-being and TCO.  
**Reduce Consumable Usage** Consumable-saving mode additionally reduces consumption and waste.

## Operations

WYSIWYG 10-inch capacitive color touchscreen: - Realtime display of remaining print capacity expressed in hours and number of messages - Integrated assistance and alert system - Simplified message printing and management - Creation of user profiles - Tracking of consumption and printer availability

Message library up to 1,000 messages

Automatic selection of fonts, depending on print speed and printhead/object distance.

Specific date management (rounding date function)

Parent/child connectivity.

Jet Speed Control guarantees marking quality

Printhead with embedded intelligence for high marking quality and reduced maintenance.

Broad range of inks: - Multi-use - High performance - Alcohol based - Ketone-free - MEK-free

Sealed 0.8-liter cartridges with fool proofing system

Compact and modular ink circuit for better thermal management and controlled additive consumption

100% front access modular ink circuit for a simplified preventive maintenance

Remote Services including our Virtual Assistant for 24/7 self-troubleshooting and how-to videos

Quick connect/disconnect of accessories (photocell, alarm and encoder)

Enhanced native connectivity including USB, Ethernet, serial and a configurable M12 connector for I/O

## Print Features

Mono-jet printhead

G head printing resolution: 71 dpi

M head printing resolution: 115 dpi

Up to 5 lines of print

Print speed: up to 6.6 m/s

Font height from 5 to 32 dots

Character height: from 1.2 to 11.2 mm

Wide choice of 1D and 2D barcodes: - EAN8/EAN13/UPCA/UPCE barcodes, code 39, interleaved 2 of 5, Datamatrix, QR code

Wide choice of characters: - Latin, Arabic, Cyrillic, Greek, Japanese, Chinese, Hebrew, Korean...

## Other Characteristics

Weight: 25 kg

Table-top or vertical mounting

Ultra-flexible 3-meter umbilical cable

Stainless steel cabinet and printhead case

Dust/humidity protection rating: IP55 not requiring plant air

Operating temperature range: 0° to 40° C, depending on ink used

Humidity: 10% to 90% non-condensing

Electrical power supply: 100 - 240 V, 1.6 Amp, frequency 50/60 Hz

## Options

Ultra-flexible 6-meter umbilical cable

IP66 protection (plant air required)

TCO option for lower additive consumption: - At 20°C less than 3,5 cc/h for MEK-based ink or less than

2cc/h for MEK-free ink

Printhead pressurization kit

Many I/O possibilities including a configurable single point connector (24 pins)

## Accessories

Printer supports: - Stainless steel or aluminum stand - Table or wall mounting bracket

Printhead supports: - Stainless steel stand - Choice of brackets

Photocells, encoders, alarm beacons (24 V)

Set of pre-cabled connectors M12, Ethernet IP66

## Software

Fully compatible with CoLOS Version 6.3 Service Pack onwards

Logo creation with CoLOS Graphics software

## Material Types

Tube laminates

Tetrapak bricks

Stick packs

Seal wrappers

Seal bags

Pipes

Pouches

Metal industrial parts

Medicines

Machined metal parts

Latex products

Jars

Hoses

High barrier films

Formed metals parts

Electrical devices

Electric wires

Eggs

Decorative labels

Customized packages

Corrugate

Copper wires

Copper cables

Containers

Cardboard boxes

Caps

Cans

Cables

Bulbs

Bottles

Aluminium foil lids

## Industries

Beer & cider  
Automotive  
Aerospace  
Soft drinks  
Snack food  
Pharmaceuticals  
Pet food  
Personal care  
Oil and gas  
Industrial components  
Food  
Extrusion  
Electronics  
Electrical  
Egg  
Dairy  
Cosmetics  
Construction  
Confectionery  
Beverage

Please [contact Pro Pac](#) or call 888-318-0083 for your printing and date-coding equipment.