



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Markem-Imaje SmartDate X65-128 Thermal Transfer Printer



## At a Glance

- High-quality coding on flexible film packaging up to 400 packs per minute
- Intuitive 10.1 inch user interface makes daily operations easy
- Designed for wide format printing, up to 128 mm x 150 mm

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## High-Quality Coding Designed for Wide Format Printing

Designed for wide format printing applications, the SmartDate X65-128 delivers high-resolution coding on flexible film packaging as fast as 400 packs per minute. Its printhead characteristics make it ideal for wide messages such as ingredient and nutritional coding.

Its fully intuitive 10.1" user interface makes daily operations easy and straightforward while providing the most valuable information you need to optimize and improve your Overall Equipment Effectiveness (OEE) through MI Sigma reporting.

## Benefits

**Delivers Extended Performance** Up to 128 mm x 150 mm printing area capacity delivers twice the amount of variable print versus a standard coder thus reducing costs.

**Drives Efficiency** Minimizes time and effort by printing multiple codes on multi-lane packaging lines on demand, quickly and efficiently.

**Ensures Code Quality** Automatic printhead setup optimizes printhead lifetime and allows for dead-dot monitoring.

**Achieves Superior Printing Speeds** Print speed can be set from 10 mm to 700 mm per second allowing for more than 400 printed packs per minute at 300 dpi.

## Enhanced SmartDate Experience

**Optimized Tracking of OEE Data** Coder can be configured to monitor your 5 most important production

metrics directly from your home screen e.g., pack rate, throughput, availability.

**Tutorials to Facilitate Daily Activities** Animated help and how-to tutorials provide guidance on setup and daily maintenance procedures to ensure consistent print quality.

**Profile Configurator for Error-Free Operation** Configurable profile password function (operator, supervisor and engineer) manages access and limits human-related errors.

## Cost-Effective Reliability

**Zero Preventive Maintenance** Robust direct ribbon drive and cassette design contain no wear parts.

**All-in-One Printer for Enhanced Flexibility** Both intermittent and continuous configurations with a 53 mm printhead are available on the same coder.

**Up to 15% More Codes per Roll** Large choice of ribbon rolls based on your packaging type and needs.

## Operations

User Interface: - 10.1" full colour 1024 x 600 touch screen - Message selection - Variable data entry - Diagnostics - System setup

MI Sigma functionality

Advanced health and availability monitoring

Configurable user home screen

Animated Help Tutorials: - Ribbon fitting - Printhead cleaning - Printhead replacing

Simple print and image adjust

Parent/Child function to allow parent control for up to 7 children

Configurable password protection capability

WYSIWYG print preview of printed message, real-time display of remaining print capacity expressed in hours and number of prints

Full diagnostics (pack rate, speed)

Robust LED status indicators on the printer

Webbing diagram for fast ribbon changes

Hardware Interface: - Inputs: Print go and 1 configurable input - Outputs: Fault, warning, and 2 configurable outputs

Software Interface: - USB for downloading images, settings and data files - RS232, Ethernet communications standard - Communications protocols for PCs, PLC and packaging machines, including full remote control web server

## Print Features

Print speed: - Intermittent: Up to 700 mm/s - Continuous: 10 to 700 mm/s

Print Area: - Intermittent: 128 mm x 75 mm - Continuous: 128 mm x 150 mm

Print features: - Automatic printhead setup - Detect: Dead-dot detection - Quick change printhead - Combined intermittent and continuous printing - Easily change from left to right hand with no additional parts - Gap between prints: 0.5 mm - Automatic shift codes and serial numbers - Multiple variable user input fields with alphanumeric texts - High pack-rate mode

Ribbon saving mode: - Radial ribbon save - Interlaced mode - Radial mode 1 - Radial mode 2 - Radial interlaced - Whitespace - Radial whitespace - Step advance

Print specifications: - Full true type font support, including non-Roman characters and symbols -

Printing of real-time clock, dates and auto updating best before dates

Barcodes: - ITF, Code 39, Code 128, EAN 128, EAN 8, EAN 13, UPC A, UPC E, RSS linear, PDF 417, GS1 DataMatrix, QR and Composite RSS

## Other Characteristics

Thermal transfer ribbon available in a variety of grades and colors

Maximum ribbon length: up to 900 m

Minimum ribbon width: 55 mm

Maximum ribbon width: 130 mm

Weight: - Printer: 10.2 kg - Color controller: 4.8 kg

Power: 90 – 264 V with automatic switching; frequency 47/63 Hz; power 150 VA

Air supply: 6 bar/90 psi (maximum) dry, uncontaminated

Air consumption: Down to 0.4 ml/print at 2.5 bar

Operating temperature range: 0 to 30°C

Humidity: 10% to 90% non-condensing

## Options

Promotional coding

WEB Browser and Virtual Network Computing support

IP protection kit for installed SmartDate X65-128

## Accessories

Mounting bracket

Encoders

## Software

Included CoLOS Free 6.0 for design of simple messages

## Material Types

Stick packs

Seal wrappers

Seal bags

Pouches

Metalized labels

High-barrier films

Decorative labels

## Industries

Pharmaceuticals

Snack food

Pet food

Food

Cosmetics

Dairy

Confectionery

Beverage

Please [contact Pro Pac](#) or call 888-318-0083 for your printing and date-coding equipment.