



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# OK Supersealer SB40 Band Sealer



## At a Glance

- Four heating capsules increase heat capacity, sealing heavy gauge films with at higher speeds
- High speeds up to 100 feet per minute with reliable efficiency
- SB40 is constructed with stainless steel

Buy your [stand-up pouches and bags](#) from us, and get a discount on this OK band sealer!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Increased Heat for High-Speed Sealing of Heavy Films

The OK Supersealer SB40 rotary band sealer continuously seals a wide range of bag materials at high speeds and remarkable efficiency. The SB40 has four heating capsules. With increased heat capacity, this machine is capable of sealing with a higher speed and heavy gauge films. The heavy duty stainless steel construction with proven band sealing technology and operator friendly controls ensures continuous high performance in demanding production requirements.

## Features & Benefits

**Stainless Steel Finish:** Clean and durable, preferred in food and other industries

**No-Tool Band Change:** Simple to maintain

**Heavy-Duty Band Sealing Technology:** Unique visually automatic band tensioning system

**Variable Speed:** Ease of matching conveyor speed for flexibility

**Closed Loop Temperature Control:** Accurate and consistent sealing temperature

**Motorized Pedestal:** Height adjustment with a button simplifies multiple bag size sealing runs

**Easy Lift Front Cover:** On-top access to all components means faster maintenance

## Specifications

Bag/Pouch Size: All sizes

Bag/Pouch Material: Heat seal up to 40 mil

Belt Speed: Up to 100 ft/min (30 m/min)

Seal Width: 7/16" (11mm)

Machine handing: Right to left or left to right

Power Requirements: 110 VAC, 1 Ph, 60 Hz, 10 Amp 220 VAC, 1 Ph, 50 Hz, 7 Amp CE Marked

Pneumatic: Not required on standard operation, 80-160 psi required for trim remover

## Options

Bag Top Trimmers: Stationary blade and rotary blade trimmer meets all application requirements

Bag Trim Remover: Standard trim remover can remove up to 3" or 5" of trim

Automatic Infeed: T Pak Infeed into Supersealer for high speed systems

Conveyors: 6" wide x 8' long conveyors stocked, other conveyor sizes custom built

Date/Lot Coders: Emboss coder and ink wheel coder provide up to 32 characters per line, both with up to two lines of code

Bag Fillers: Scales, augers, robotics, and automatic bag loaders to create a seamless packing line

Washdown and Corrosive Washdown: For wet and corrosive environments

Deduster for Dusty Environments: Removes dust that creates barriers from seal area so that bag can be sealed

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.