



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

OK Supersealer SS1 & SS2 Hot Air Bag Sealers



At a Glance

- Hot air bag sealer continuously seals a wide range of bag materials
- No teflon bands
- State-of-the-art process controls
- 120 feet per minute
- Rugged painted or stainless steel construction

Buy your [stand-up pouches and bags](#) from us, and get a discount on this OK hot air sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Super High-Speed Bag Sealing with Hot Air - No Teflon Bands

The Supersealer SS1 and SS2 hot air bag sealers utilize hot air to continuously seal a wide range of bag materials at high speed and remarkable efficiency. The advanced airflow, sophisticated controls, and rugged painted or stainless construction ensures continuous uptime performance in all applications.

Features & Benefits

Hot Air Sealing Technology: Optimum seal quality at low maintenance, no Teflon bands!

Variable Speed: Ease of matching conveyor speed for flexibility

Closed Loop Temperature Control: Accurate and consistent sealing temperature

Motorized Pedestal: Height adjustment with a button simplifies multiple bag size sealing runs

Specifications

Bag/Pouch Size: All sizes

Bag/Pouch Material: Heat seal up to 40 mil

Belt Speed: Up to 120 ft/min (36.5 m/min)

Seal Width: 1/4" (6mm) standard, 1/3" (9mm) or 1/2" (12mm) optional

Machine handing: Right to left or left to right

Power Requirements: 110 VAC, 1 Ph, 60 Hz, 10 Amp. 220 VAC, 1 Ph, 50 Hz, 7 Amp.

Pneumatic: Not required on standard operation, 80-160 psi required for Jet Flow Trim Remover

SS2WD Wash Down Version

The heavy-duty Supersealer SS2WD Washdown Hot Air Sealer combines stainless steel construction with proven band sealing technology and operator friendly controls ensures continuous duty performance in demanding applications.

Options

Bag Top Trimmers: Stationary blade and rotary blade trimmer meets all application requirements

Bag Trim Remover: Standard trim remover can remove up to 3" or 5" of trim

Automatic Infeed: T Pak Infeed into Supersealer for high speed systems

Conveyors: 6" wide x 8' long conveyors stocked, other conveyor sizes custom built

Date/Lot Coders: Emboss coder and ink wheel coder provide up to 32 characters per line, both with up to two lines of code

Bag Fillers: Scales, augers, robotics, and automatic bag loaders to create a seamless packing line

Washdown and Corrosive Washdown: For wet and corrosive environments

Deduster for Dusty Environments: Removes dust that creates barriers from seal area so that bag can be sealed

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.