



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

OK Supersealer T-Pak 500 Conveyor Bag Sealer System

At a Glance

- OK Super Sealer integrated with flat bed conveyor
- State of the art process controls
- Painted, stainless steel, and washdown configurations

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Quickly Convey Bagged Products Directly into the Sealer

OK Sealer semi-automatic T-PAK 500 system comes equipped with a Supersealer medical band sealer, an optional T-PAK Infeed device, SST Top Trimmer and a Trim Remover.

The OK T-PAK 500 band sealing system is assembled to seal any kind of pouch material for the medical device industry. This system can be used in combination with automatic baggers or multiple operators on one line. Available in stainless steel construction.

These band sealers are commonly used for applications requiring the product to lay flat.

All the sealers are available in right to left or left to right configurations with various options. It is CE marked, and runs on 110 or 220 volt, and can be plugged into any wall socket.

These band sealers meet ISO 11607-2, ISO 13485, ISO 9001, and EN 868 specifications.

Features & Benefits

Band Sealing Technology: Can seal multiple materials consistently, because the band supports pouch/bag material through sealing process.

Variable Speed: Ease of matching conveyor speed for flexibility.

Closed Loop Temperature Control: Accurate and consistent sealing temperature.

Touch Panel Monitor: Operators, Managers, QC personnel can always see all variables of the machine at all times both set and actual.

Recipes in PLC: Pouch/Bag changeover made easy with menu and load up the next pouch/bag parameters with a touch of a button. The PLC can hold up to 65 recipes.

Easy Lift Cover: No tool required for band change with easy access.

Motorized Pedestal: With a touch of a button, for height adjustment, simplifying multiple pouch/bag size applications.

Plugs into any Wall Plug: Minimal utility requirements.

Out of PLC Parameter Settings: No pouch/bag will be sealed out of its parameter settings. The machine will run in reverse if out of its parameters.

IQ/OQ Sample documents: Information for the small to mid size companies that may require an introductory guideline.

Packaging of Terminally Sterilized Medical Devices: Meeting: ANSI/AAMI/ASTM, ISO 11607-2, ISO 13485, ISO 9001 and EN 868 standards for compliance.

Specifications

Stainless Steel Finish: Clean and durable for any clean room

Bag/Pouch Material: Heat seal up to 20+ mils and will seal a wide range of material such as Poly/Poly, Tyvek, Mylar, Pet Coated Tyvek, Paper/Poly, Laminated Foil and Metalized Foil

Speed: Up to 60 ft/min or 18 m/min belt speed. Other speeds upon request

Seal Width: 7/16" (11mm)

Heating Bars: One pair (1) 7" (17.78cm)

Cooling Bars: One pair (1) 5" (12.7cm)

Machine Handing: Right to Left or Left to Right

Power Requirements: 110 VAC, 1 Ph, 60 Hz, 10 Amp. 220 VAC, 1 Ph, 50 Hz, 7 Amp. CE Marked

Pneumatic: 80-100 psi clean dry air

PLC Control: Touch Screen

Options

Bag Top Trimmers: Stationary blade and rotary blade trimmer meets all application requirements

Bag Trim Remover: Standard trim remover can remove up to 3" or 5" of trim

Automatic Infeed: T Pak Infeed into Supersealer for high speed systems

Date/Lot Coders: Emboss coder and ink wheel coder provide up to 32 characters per line, both with up to two lines of code

Bag Fillers: Scales, augers, robotics, and automatic bag loaders to create a seamless packing line

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.