



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

APM HCBS-1/4 CT Dual Horizontal Conveyorized Band Sealer with Trimmer



At a Glance

- Built with a conveyor, dual heating elements, dual cooling zones, and a bag top trimmer
- Great for flat products and higher production speeds
- Unique trim after seal system assures clean, straight trim
- Constant secure 1/8, 1/4, or 3/8 inch seals

Buy your [stand-up pouches and bags](#) from us, and get a discount on this APM band sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Horizontal Conveyorized Band Sealer with Dual Heating and Cooling Zones

APM HCBS-1/4 CT high-speed horizontal conveyorized bag sealer is built with a conveyor, dual heating elements, dual cooling zones, and a bag top trimmer. Great for flat products and higher production speeds.

The unique trim after seal system assures clean, straight trim directly at seal edge. Designed to seal bags for a wide range of products including: tortillas, medical, candy, paper goods, textiles, poultry, bakery, toys, crafts, garden, pet supplies, decorative, mailroom, electronics, jewelry, parts kits, and many more!

Features

Turn one dial to change speeds

Permanent magnet DC gear motor along with full mechanical linkage creates positive sealer to conveyor synchronization

Variable speeds up to 540 inches per minute (45 fpm) with ultra-quiet DC gear motor

Constant secure seals of 1/8", 1/4", or 3/8" wide

Special heavy duty 1" wide wear-resistant laminated Teflon bands

Dual digital temperature controls with PID Auto tune maintains consistent heat and assures quality hermetic seals

Dual 5" long heating zones (10" total) and dual 5" long cooling zones (10" total) for sealing heavier films at high production rates

Sealing temperatures up to 500F

Hard chrome plated sealing bars followed by nickel plated cooling bars allow for maximum wear resistance

Bag top trimmer

Angle adjustable all-welded steel base stand allows tilting of the conveyORIZED sealing system, assuring uniform packages.

Adjustable height bag leveling shelf maintains top portion of bag on level plane, assuring durable flat seal.

Lower carry belts

6" wide x 8' long variable speed conveyor with fully adjustable stainless steel guide rails

Crank handle on sealing assembly floor stand to adjust sealing height

Vacuum system for trim scrap removal

USDA approved

Options

3", 6", 9", or 12" wide belted overhead compression assembly to remove excess air from bagged product before sealing

Stainless steel base stand

One-line embossing coder for product marking

Kevlar sealing bands for added durability

Supported Bag Materials

Polyethylene

Polypropylene

Polyester

Tyvek

Laminates

Nylon

Foils

Shrink films

Specifications

Electrical: 110 VAC, 10 to 20 amps, 60 cycle

Air: No compressed air required

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.