

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com Contact

Our Packaging Experts solutions@propac.com 888-318-0083

APM ATS-IMP-1/8-16 and 5/16-16 Table-Top Bag Sealers



At a Glance

- Table top impulse sealers
- Adjustable dwell timer, impulse timer, and cooling timer
- Foot pedal start switch

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Simple-to-Use Table Top Impulse Bag Sealer

APM ATS-IMP-1/8 and 5/16 table top impulse sealers are designed to seal loaded bags of a wide range of products including: food, candy, paper goods, textiles, poultry, bakery, toys, crafts, garden, pet supplies, decorative, automotive, electronics, jewelry, mailroom, parts kits, and many more. Simply load the bag, place the bag on the front tray, and depress the foot-switch to activate the sealing bar.

Features of the ATS-IMP-1/8-16

Impulse sealing with 1/8" or 1/4" wide seals without trim Adjustable dwell timer, impulse timer, and cooling timer for sealing different thicknesses and materials Adjustable front feeder tray Foot pedal start switch Heavy gauge welded and painted steel construction

Features of the ATS-IMP-5/16-16

Seals and trims polyethylene film only Smokeless and odorless 1/8" wide trimmed seal Preheat design, no warm up time required Scrap removal and scrap net Adjustable dwell timer, impulse timer, and cooling timer for sealing different materials Adjustable front feeder tray

Bag Specifications for the ATS-IMP-1/8-16

Polyethylene Polypropylene Foil Nylon Coextrusion Cellophane Polylaminates Poly-coated paper materials Bags 2" to 16" wide

Bag Specifications for the ATS-IMP-5/16-16

Polyethylene only Bags 2" to 16" wide

Options for Both Models

Wider sealers for wider bags

Specifications for Both Models

Electrical: 110 VAC, 15 amps, 60 cycle (220V available) Air: 80-90 psi compressed air required

Please contact Pro Pac or call 888-318-0083 for your bag sealing equipment.