



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# APM VBS-1/8 TX Vertical Band Sealer with Trimmer



## At a Glance

- Vertical band sealing system without a product support conveyor
- TX models are built with an internal carry belt system
- Supports products weighing up to 1 pound
- Simple interface and speed adjustment

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Vertical Band Sealer for 1-Pound Products with Trimmer

APM VBS-1/8 TX vertical band sealing system is built with an internal lower carry belt system that supports products weighing up to 1 pound. The VBS-1/8 TX sealing assembly is mounted on 4' floor stand with simple height adjustment to meet production and operator height requirements. A bag top trimmer and vacuum system for scrap removal comes standard.

## Features

- Simple interface and speed adjustment
- Smokeless and odorless sealing and trimming
- Variable speeds up to 540 inches per minute (45 fpm)
- Ultra-quiet gear motor
- Constant secure seals of 1/8", 1/4", or 3/8" wide
- Special heavy-duty 1" wide wear-resistant laminated Teflon bands
- Digital temperature control with PID Autotune maintains consistent heat and assures quality hermetic seals
- 5" long heating zone and 5" long cooling zone provides flexibility in sealing of difficult materials
- Sealing temperatures up to 500F
- Hard chrome-plated sealing bars and nickel-plated cooling bars provide maximum wear resistance
- USDA approved

## Options

One or two line embossing coder for product marking  
Casters for easy positioning (shown)

## Designed to Seal These Materials

Polyethylene  
Polypropylene  
Tyvek  
Foil/PE  
Polylaminates  
Nylon  
Coextrusion  
Poly-coated paper materials

## Specifications

Electrical: 110 VAC, 10 amps, 60 cycle  
Air: No compressed air required

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.