



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# APM VBS-3/8 Vertical Band Sealer



## At a Glance

- Vertical band sealing system without a product support conveyor
- Portable, mounted on a 4 foot high adjustable floor stand
- Simple interface and speed adjustment

Buy your [stand-up pouches and bags](#) from us, and get a discount on this APM band sealer!

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Portable Vertical Band Sealer for Products Up to 1 Pound

The portable APM VBS-3/8 vertical band sealer is mounted on a 4' high adjustable floor stand. If needed, the heat sealing assembly can be positioned over an existing conveyor.

## Features

Variable speeds up to 540 inches per minute (45 fpm)

Ultra-quiet gear motor

Front heater On/Off switch for sealing Tyvek (front and rear heaters generate heat as required for other materials)

Constant secure seals of 1/8", 1/4", or 3/8" wide

Special heavy-duty 1" wide wear-resistant laminated Teflon bands

Digital temperature control with PID Autotune maintains consistent heat and assures quality hermetic seals

5" long heating zone and 5" long cooling zone provides flexibility in sealing of difficult materials

Sealing temperatures up to 450F

Hard chrome-plated sealing bars followed by nickel-plated cooling bars provide maximum wear resistance

Anodized aluminum chassis sealing assembly and stainless steel shafting throughout assures longevity

USDA approved

## Options

Embossing coder for product marking

## Supported Bag Materials

Polyethylene  
Polypropylene  
Polyester  
Kraft/PE  
Tyvek  
Polymylar  
Foil/PE  
Cryovac  
Coextrusions  
Polylaminates  
Military Specs  
Nylon

## Specifications

Electrical: 110 VAC, 10 amps, 60 cycle

Air: No compressed air required

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.