



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

APM VCBSDM-1/4 TX Vertical Conveyorized Band Sealer with Trimmer



At a Glance

- Specifically designed to seal extremely close to the product
- TX model sealers have scrap removal system trims and sucks away the scrap
- 12 inch x 5 foot interfaced variable-speed support conveyor

Buy your [stand-up pouches and bags](#) from us, and get a discount on this APM band sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Close to Big Bulky Products and Trim the Scrap

The APM VCBS-1/4 TX band sealer is specifically designed to allow the seal to be extremely close to the product. The synchronized conveyor brings the bagged product into the seal head. After sealing, the scrap removal system trims and sucks away the scrap. This heavy-duty band sealer is ideal for sealing bulk packs of toilet paper, paper towels, diapers, and many other large products.

Features

12"W x 5'L interfaced variable-speed support conveyor with fully-adjustable stainless steel guide rails

Adjustable height sealing assembly floor stand with crank handle

Vacuum system for trim scrap removal

Variable speeds up to 540 inches per minute (45 fpm)

Ultra-quiet gear motor

Special heavy-duty wear-resistant laminated Teflon bands produce quality 1/8", 1/4", or 3/8" seals

Digital temperature control with PID Autotune maintains consistent heat and assures consistently hermetic seals

5" long heating zone and 5" long cooling zone provides flexibility in sealing of difficult materials

Sealing temperatures up to 500F

Hard chrome-plated sealing bars followed by nickel-plated cooling bars provide maximum wear resistance

USDA approved

Options

Casters for easy positioning (shown)

Supported Bag Materials

Polyethylene (PE)

Polypropylene (PP)

Tyvek

Foil/PE

Polylaminates

Nylon

Coextrusion

Poly-Coated Paper Materials

Specifications

Electrical: 110 VAC, 10 amps, 60 cycle

Air: No compressed air required

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.