



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

APM VCBSDM-1/8 TX Vertical Conveyorized Band Sealer with Trimmer



At a Glance

- Specifically designed to seal extremely close to the product
- TX model sealers have scrap removal system trims and sucks away the scrap
- 6 inch x 5 foot interfaced variable-speed support conveyor

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Heavy-Duty Band Sealer with Trimmer for Products Over 1 Pound

The APM VCBS-1/8 TX vertical conveyorized band sealer is the industry standard for reliably sealing just about any bagged product in all kinds of bag materials. The VCBS TX series has a bag top trimmer and scrap removal system. The synchronized support conveyor carries products over 1 pound through the seal head assembly.

Features

6"W x 5'L interfaced variable speed support conveyor with fully adjustable stainless steel guide rails

Adjustable height sealing assembly floor stand with crank handle

Vacuum system for trim scrap removal

Smokeless and odorless sealing and trimming

Variable speeds up to 540 inches per minute (45 fpm)

Ultra-quiet gear motor

Special heavy duty wear-resistant laminated Teflon bands produce quality 1/8", 1/4", or 3/8" seals

Digital temperature control with PID Autotune maintains consistent heat and assures consistently hermetic seals

5" long heating zone and 5" long cooling zone provides flexibility in sealing of difficult materials

Sealing temperatures up to 500F

Hard chrome-plated sealing bars followed by nickel-plated cooling bars provide maximum wear

resistance
USDA approved

Options

One or two line embossing coder for product marking
Casters for easy positioning (shown)
Infeed conveyor support heavy or bulky packages for final seal and trim

Supported Bag Materials

Polyethylene
Polypropylene
Tyvek
Foil/PE
Polylaminates
Nylon
Coextrusion
Poly-coated paper materials

Specifications

Electrical: 110 VAC, 10 amps, 60 cycle
Air: No compressed air required

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.