



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Emplex MPS 6140 Table-Top Band Sealer



## At a Glance

- Industrial strength table-top sealer at a great price
- Delivers fast, precise, and strong seals on bags and stand-up pouches
- Seals bags weighing up to 8 ounces
- Industrial PC and 5.7 inch color touch-screen interface

Buy your [stand-up pouches and bags](#) from us, and get a discount on this Emplex band sealer!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Industrial Strength Table-Top Band Sealer

The Emplex MPS 6140 table-top band sealer is an industrial-strength table top bag sealer capable of sealing bags up to 8 ounces in weight and film up to 6 mil in thickness (3 mil maximum when gusseted). Designed for 24/7 operation, this small yet heavy-duty sealer is suitable for many production environments.

Emplex MPS 6140 table-top band sealers offer you high-quality and reliability at a great price. Key design features include a unique Teflon band tensioner, tool-less access to the seal section, removable sealing sections, the ability to easily add options to the machine in the field, customizable stands, and much more.

Emplex MPS 6140 sealers deliver fast, precise, and strong seals on bags and stand-up pouches. With true plug and play capabilities the MPS 6140 offers reliable, easy-to-use performance for a variety of bagging operations in nearly any production environment. The MPS 6140 is a low maintenance machine with easy access to the seal section, and has modular components for easy expandability as your production needs increase.

## Comprehensive Controls that Are Simple to Use

The MPS 6140 band sealer comes standard with an advanced touchscreen interface that simplifies setting, monitoring, and tracking crucial controls such as heat, seal pressure, and speed. Settings are available in imperial or metric measurements. The easy-to-use touch-screen display provides routine maintenance, troubleshooting data, and many selectable preferences and management features.

## Features

Modular, made-to-order, user selections for electrical, infeed direction, sealer orientation, seal widths, and seal band pressure rollers  
Easy access to sealing section  
5 minute or less changeover of seal bands  
Cool down mode  
Clear Lexan guard of seal section  
Small footprint  
Continuous  
Flexible  
Plug and play

## Controller

Industrial PC and 5.7" color touchscreen interface  
Single point setting for speed, temperature, and pressure  
Recipe management and selection for different materials and products  
Production and user activity reporting and management tools  
Multi-language preference settings  
Diagnostics and background monitoring of key processes and components to prevent machine damage or product loss  
Maintenance alerts

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.

## Specifications

Electrical	115/230 volts, 12 amps, 50/60hzs
Air	No air required
Motor	1/4HP PWM PMDC
Sealer Duty	Continuous
Infeed Direction	Right to left or left to right
Sealer Orientation	Vertical or horizontal
Sealer Band	Teflon
Pressure Rollers	Stainless steal or rubberized
Sealing Width	Choice of 1/8" (3.2mm), 1/4" (6.35mm), 3/8" (9.5mm), 1/2" (12.7mm), 3/4" (19.05mm)
Heating and Cooling Capacity	5" (12.7cm) heating bars, 5" (12.7cm) cooling bars
Variable Speed	Up to 1000" (25mm) per minute
Temperature Range	0-392F (0-200C)
SPL	60 db
Washing / Cleanroom	Standard wipe down cleaning