



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Emplex MPS 6140 Table-Top Band Sealer



At a Glance

- Industrial strength table-top sealer at a great price
- Delivers fast, precise, and strong seals on bags and stand-up pouches
- Seals bags weighing up to 8 ounces
- Industrial PC and 5.7 inch color touch-screen interface
- Up to 300 inch (762cm) per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Industrial Strength Table-Top Band Sealer

The Emplex MPS 6140 table-top band sealer is an industrial-strength table top bag sealer capable of sealing bags up to 8 ounces in weight and film up to 6 mil in thickness (3 mil maximum when gusseted). Designed for 24/7 operation, this small yet heavy-duty sealer is suitable for many production environments.

Emplex MPS 6140 table-top band sealers offer you high-quality and reliability at a great price. Key design features include a unique Teflon band tensioner, tool-less access to the seal section, removable sealing sections, the ability to easily add options to the machine in the field, customizable stands, and much more.

Emplex MPS 6140 sealers deliver fast, precise, and strong seals on bags and stand-up pouches. With true plug and play capabilities the MPS 6140 offers reliable, easy-to-use performance for a variety of bagging operations in nearly any production environment. The MPS 6140 is a low maintenance machine with easy access to the seal section, and has modular components for easy expandability as your production needs increase.

Comprehensive Controls that Are Simple to Use

The MPS 6140 band sealer comes standard with an advanced touchscreen interface that simplifies setting, monitoring, and tracking crucial controls such as heat, seal pressure, and speed. Settings are available in imperial or metric measurements. The easy-to-use touch-screen display provides routine maintenance, troubleshooting data, and many selectable preferences and management features.

Features

Modular, made-to-order, user selections for electrical, infeed direction, sealer orientation, seal widths, and seal band pressure rollers
Easy access to sealing section
5 minute or less changeover of seal bands
Cool down mode
Clear Lexan guard of seal section
Small footprint
Continuous
Flexible
Plug and play

Controller

Industrial PC and 5.7" color touchscreen interface
Single point setting for speed, temperature, and pressure
Recipe management and selection for different materials and products
Production and user activity reporting and management tools
Multi-language preference settings
Diagnostics and background monitoring of key processes and components to prevent machine damage or product loss
Maintenance alerts
Pictorial maintenance guides and instructional tutorials

Options

Stainless sealer band
Extended height stands
4" (10.16 cm) additional throat depth

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.

Specifications

Sealer Duty	Continuous
Infeed Direction	Right to left or left to right
Sealer Orientation	Vertical or horizontal
Sealer Band	Teflon, easy access tool-less changeover
Pressure Rollers	Stainless steal or rubberized
Sealing Width	Choice of 1/8" (3.2mm), 1/4" (6.35mm), 3/8" (9.5mm), 1/2" (12.7mm), 3/4" (19.05mm)
Sealing Throat Depth	3.5" (88mm)
Variable Speed	Up to 300" (762cm) per minute
Temperature Range	0-392F (0-200C)
Heating and Cooling	5" (12.7cm) heating bars, 5" (12.7cm) cooling bars
Washing / Cleanroom	Standard wipe down cleaning
Frame	304 stainless steel
SPL	60 db
Motor	1/4HP PWM PMDC
Electrical	110V 12A or 220V 6A
Air	No air required