



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Emplex VacPack VP Vacuum Sealing Gas Flushing Impulse Sealer



## At a Glance

- Robust, stainless steel food grade sealer
- Modified atmosphere package for a wide range of product sizes, including extra wide and heavy products
- Seals any heat-sealable bag or pouch up to 12 mil in thickness

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Hermetic Impulse Bag Sealing with Gas Flushing

Emplex VacPack VP impulse sealers are robust, stainless steel food grade sealers that create a modified atmosphere package for a wide range of product sizes, including extra wide and heavy products.

VacPack sealers employ an ejector style vacuum pump and produce hermetically sealed packages on any heat sealable bag up to 12 mil/300 micron in thickness (6 mil/150 micron maximum when gusseted).

The vacuum and nitrogen gas flush system removes oxygen, resulting in longer shelf life, product integrity, and protection against discoloration. The gas flush system can create a cushion-like buffer against damage.

## Comprehensive Simple Controls

The Emplex VP impulse sealer comes standard with an advanced touchscreen PLC that simplifies setting, monitoring, and tracking crucial controls such as heat, seal pressure, and speed. Settings are available in imperial or metric measurements. The easy-to-use PLC provides routine maintenance, troubleshooting data, and many selectable preferences and management features.

## Features

Advanced, industrial touchscreen PLC with imperial or metric settings and numerous user selectable preferences and productivity management tools

Small footprint

Standalone flexibility  
Plug and play  
All machines tested to ANSI/PMMA B-155.1-2000 and CE marking standards  
All parts UL/CSA approved

## Controller

Industrial PC and 5.7" color touchscreen interface  
Single-point setting for speed, temperature, and pressure  
Recipe management and selection for different materials and products  
Production and user activity reporting and management tools  
Multi-language preference settings  
Diagnostics and background monitoring of key processes and components to prevent machine damage or product loss  
Maintenance alerts  
Pictorial maintenance guides and instructional tutorials

## Options

Additional nozzles  
Extended seal length  
Product shelf  
Washdown NEMA 4 or 4x construction

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.

## Specifications

Sealer Duty	Impulse
Vacuum / Gas Flush	Ejector style, stainless steel nozzles
Sealer Orientation	Vertical or horizontal (table top or floor stand)
Changeover	One touch removal of vacuum/gas flush tubes Easy change nichrome Easy change Teflon covers
Sealing Width	1/4" (6.35mm)
Sealing Length	24" (60.9 cm), 30" (76.2 cm) or 36" (91.4 cm)
Seal Throat Depth	5" (12.7 cm)
Washing / Cleanroom	Standard wipe down cleaning
Frame	316L stainless steel
Electrical	120V 12A or 220V 6A
Air	15 CFM 80 PSI

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.