



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Emplex MPS 6700 Medical Validatable Band Sealer with Conveyor



At a Glance

- Precise process control for temperature, pressure, speed, and seal quality
- For packaging medical instruments, disposable items, and sterile products
- Seals bags weighing over 2 lbs utilizing a support conveyor

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Hermetically Seal Medical Products Over 2 Pounds with Support Conveyor

Consistent, validatable sealing is crucial when packaging sterile products. Emplex MPS 6700 validatable continuous band sealers deliver precise process control for temperature, pressure, speed, and seal quality. All validatable medical systems include visual and audio alarms for deviations in heat, speed, and pressure. Standard easy to use touch-screen display provides advanced calibration, data collection, and process management control. The industrial PC provides routine preventative maintenance, troubleshooting data and many user selectable preferences in imperial or metric measurements.

The Emplex MPS 6700 offers true plug and play capabilities for any clean room or sterile packaging environment. It is a reliable, easy-to-operate, low maintenance machine with easy access to the seal section and modular components for easy expandability as production needs increase. The MPS 6700 is a continuous sealer capable of creating validatable seals at speeds up to 1000" per minute depending on bag width and thickness.

The MPS 6700 is built for bags weighing more than 2 lbs, utilizing a stainless steel, medical grade 6 inch x 6 foot conveyor and guide rails. The standard conveyor accommodates many bag sizes. Custom conveyors are available to accommodate any size bag or weight.

Modular and Customizable

Because your bag sealing needs are unique, the MPS 6700 is made to order with numerous user-

selectable specifications and a comprehensive feature set. At no additional charge, you can configure your bag sealer's infeed direction, sealer orientation, sealing width, type of pressure rollers, and electrical supply.

Additional customizable options and equipment add-ons are available at competitive prices. Common upgrades include compression belts to remove ambient air or vacuum and gas flush systems for additional product protection and purity.

Films

The MPS 6700 validatable medical sealer provides fast, precise, strong seals on tyvek, foil, poly bags and on all hermetic materials typically used for packaging medical instruments or disposable devices such as IV bags, suture kits, medical draping, bandages, gauze, and other sterile products.

Features

Consistent, validatable sealing

Precise management and control of sealing process

Stainless steel, medical grade construction

Modular, made-to-order, user selections for electrical, infeed direction, sealer orientation, seal widths, seal band, pressure rollers

Advanced, industrial touchscreen PLC with imperial or metric settings and numerous user selectable preferences and productivity management tools

Tool-less access to sealing section

Seal band changeover in 5 minutes or less

Cool down switch prolongs life of seal bands

Clear Lexan guard for safe monitoring of seal section

Small footprint

Standalone flexibility

Plug and play

All machines tested to ANSI/PMMI B155.1-2000 and CE marking standards

All parts UL/CSA approved

Continuous band sealer for optimum performance, strong seals and long life

Controller

Industrial PC and 5.7" color touchscreen interface

Single point setting for speed, temperature, and pressure

Recipe management and selection for different materials and products

Production and user activity reporting and management tools

Multi-language preference settings

Diagnostics and background monitoring of key processes and components to prevent machine damage or product loss

Preventative maintenance reminders

Pictorial maintenance guides and instruction tutorials

Options

Bag top trimmer

Exair trim scrap removal system

Emboss coder

Ink jet printers
 Robotic handling systems
 Automatic bag hangers and openers
 Stainless steel sealer band
 4" (10.16cm) additional throat depth
 Heavy-duty and specialized conveyors in multiple sizes and configurations
 Table-top frame and extended frame heights
 Washdown construction

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.

Specifications

Sealer Duty	Continuous
Infeed Direction	Right to left or left to right
Sealer Orientation	Vertical or horizontal
Sealer Band	Teflon, easy access tool-less changeover
Pressure Rollers	Stainless steel or rubberized
Sealing Width	Choice of 1/8" (3.2mm), 1/4" (6.35mm), 3/8" (9.5mm), 1/2" (12.7mm), 3/4" (19.05mm)
Seal Throat Depth	3.5" (89mm)
Food Grade Conveyor	Stainless steel 6" x 6' (15.2cm x 182.9 cm) standard on MPS 6700
Variable Speed	Up to 500" (1270cm) per minute
Height Adjustment	Crank
Temperature Range	0-392F (0-200C)
Heating and Cooling	5" (12.7cm) heating bars, 5" (12.7cm) cooling bars
Washing / Cleanroom	Standard wipe down cleaning
Frame	304 stainless steel frame and legs
SPL	60 db
Motor	1/4HP PWM PMDC
Electrical	110V 12A or 220V 6A
Air	No air required