

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com Contact Our Packaging Experts solutions@propac.com 888-318-0083

Emplex MPS 7700 Medical Validatable Band Sealer with Heavy-Duty Conveyor



At a Glance

- Speeds of up to a super-fast 800 inches per minute
- Quickly seals any heat sealable bag or pouch up to 12 mil in thickness
- Seals bags over 2 lbs with stainless steel, food grade
 6 inch x 6 foot support conveyor

Buy your stand-up pouches and bags from us, and get a discount on this Emplex band sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast Medical Bag Sealing with Support Conveyor for Heavier Products

The Emplex validatable MPS 7700 sets the standard for high-speed, heavy-duty medical bagging applications that require seal verification. This Emplex sealer can hermetically seal bags and pouches at speeds up to 800 inches (203.2 cm) per minute! The MPS 7700 sealer can be configured for manual, semi-automatic, or automatic loading, and can be adjusted to accommodate variations in material, ensuring reliable seal integrity on every bag. The MPS 7500 can seal any heat sealable bag or pouch up to 12 mil/300 micron in thickness (6 mil/150 micron maximum when gusseted).

With a stainless steel, medical grade 6 inch x 6 foot support conveyor, the Emplex 7700 continuous band sealer is ideal for sealing bags and pouchs weighing more than 2 lbs.

The MPS 7700 offers true plug-and-play capabilities for reliable, easy-to-use operation in any production environment.

Comprehensive Controls that Are Simple to Use

The MPS 7700 band sealer comes standard with an advanced touchscreen PLC that simplifies setting, monitoring, and tracking crucial controls such as heat, seal pressure, and speed. Settings are available in imperial or metric measurements. The easy-to-use PLC provides routine maintenance, troubleshooting data, and many selectable preferences and management features.

Modular and Customizable

The MPS 7700 is a low-maintenance machine with tool-less access to the seal section and modular components for easy expandability as production needs increase. The MPS 7700 is made to order with numerous user-selectable specifications and a comprehensive feature set. At no additional charge, you can determine your bag sealer's infeed direction, sealer orientation, sealing width, type of pressure rollers, and electrical supply. Additional customizable options and equipment add-ons are available.

Features

Modular, made-to-order, user selections for electrical, infeed direction, sealer orientation, seal widths, seal band, pressure rollers Advanced, industrial touch-screen PLC with imperial or metric settings and numerous user selectable preferences and productivity management tools Tool-less access to sealing section Seal band changeover in 5 minutes or less Cool down switch prolongs life of seal bands Clear Lexan guard for safe monitoring of seal section Small footprint Standalone flexibility Plug and play All machines tested to ANSI/PMMI B-155.1-2000 and CE marking standards All parts UL/CSA approved Continuous band sealer for optimum performance, strong seals and long life

Controller

Industrial PC and 5.7" color touch-screen interface Single point setting for speed, temperature, and pressure Recipe management and selection for different materials and products Production and user activity reporting and management tools Multi-language preference settings Diagnostics and background monitoring of key processes and components to prevent machine damamge or product loss Preventative maintenance reminders Pictorial maintenance guides and instruction tutorials

Options

Bag top trimmer Exair trim scrap removal system Emboss coder Ink jet printers Robotic handling systems Automatic bag hangers and openers Stainless steel sealer band 4" (10.16cm) additional throat depth Extended height stands Heavy-duty and specialized conveyors in multiple sizes and configurations Washdown NEMA 4 or 4x construction Vacuum and gas flushing with the 7503 Please contact Pro Pac or call 888-318-0083 for your bag sealing equipment.

Specifications

Sealer Duty	Continuous
Infeed Direction	Right to left or left to right
Sealer Orientation	Vertical or horizontal
Sealer Band	Teflon, easy access tool-less changeover
Pressure Rollers	Stainless steal or rubberized
Sealing Width	Choice of 1/8" (3.2mm), 1/4" (6.35mm), 3/8" (9.5mm), 1/2" (12.7mm), 3/4" (19.05mm)
Seal Throat Depth	3.5" (89mm)
Variable Speed	Up to 800" (203.2cm) per minute
Food Grade Conveyor	Stainless steel 6" x 6' (15.2cm x 182.9 cm) standard
Height Adjustment	Crank
Temperature Range	0-392F (0-200C)
Washing / Cleanroom	Standard wipe down cleaning
Heating and Cooling	10" (25.4cm) heating bars, 10" (25.4cm) cooling bars
Frame	304 stainless steel frame and legs
SPL	60 db
Motor	1/4HP PWM PMDC
Electrical	120V 12A or 220V 6A
Air	No air required
Model	Configuration
MPS 7500	Standard sealer
MPS 7510	Standard sealer with trimmer
MPS 7520	Standard sealer with emboss coder
MPS 7560	Standard sealer with trimmer & emboss coder