



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Q800C-MV Medical Validatable Continuous Bag Sealer



At a Glance

- Bag sealer designed specifically for the medical industry
- Validatable and calibratable across all seal parameters
- High-resolution HMI digital display integrates sealing speed, seal pressure, temperature control, process alarm settings, and password protected seal parameter recipes

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Validatable Seals up to 800" per Minute

The QuantumPak Q800C-MV continuous bag sealer is designed specifically for the medical industry. This QuantumPak bag sealer is validatable and calibratable across all seal parameters.

The Q800C-MV easy-to-operate, high-resolution HMI digital display integrates sealing speed, seal pressure, temperature control, process alarm settings, and password protected seal parameter recipes. This machine is perfect for bag and pouch sealing applications that require process validation.

The QuantumPak Q800C-MV Q800C-MV hermetically seals pillow top or gusseted bags, and a variety of materials, at speeds up to 800" per minute / 20+ bags per minute.

With its standard 7" wide fully-synchronized product conveyor, this bag sealer holds bags weighing up to 15 lbs. and up to 22" tall as standard.

The Q800C-MV sealer's rugged design and stainless-steel construction is suitable for 24/7 operation.

Features

Flow right-to-left flow standard

Detachable seal module (for faster changing of the seal bands/seal widths)

Rugged control box construction

Crank wheel height adjustment

Spring loaded pressure bars for better sealing pressure on thicker/gusseted bags

Rugged reinforced caster mounts
Heavy-duty gear box
USA manufactured controller and motors

Construction

Maximum speed: 800" per minute
Maximum temperature: 420° F
Max bag height: 22" (taller bag height capability is available)
High-resolution HMI screen for easy, intuitive operation
Data acquisition package

Options

Gas flush / vacuum system
Left-to-right flow
TIJ or CIJ printer
Zipper closer system
Compression rollers

Please [contact Pro Pac](#) or call 888-318-0083 for your bag sealing equipment.