



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Arpac 108 Intermittent Motion Shrink Bundler for Construction Industry



## At a Glance

- Designed for building industry environments
- Wraps rolls up to 24 inches OD x 48 inches in length
- Up to 20 products per minute

Buy your [shrink bundling film](#) from Pro Pac, and get a discount on this Arpac shrink bundler!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Shrink Bundler to Collate and Overwrap Food and Dairy Products

The Arpac intermittent motion shrink wrappers is specifically designed and built for building industry environments. The 108 bundler is a compact, right-angle shrink wrapping system.

## Features

Heavy-duty rugged construction for high durability and around-the-clock operation

Laser cut and CNC machined components for maximum precision and strength

Powder coat finish that provides a durable scratch resistant surface and prevents corrosion

Allen-Bradley PanelView Plus 600 operator interface with color touchscreen, message display and self-diagnostics

NEMA 12 rated main electrical cabinet

Central point lubrication simplifies preventive maintenance

Low film alert warns when a film changeover is necessary

## Options

Product hold down

Low tension film feed

Side seal assembly

Manual or automatic adjustment for side seal

Product centering device

System bypass

Film hoist  
Stainless steel construction  
NEMA 4X rated electrical cabinet  
Extended tunnel height for taller product

## Roll Products

Rolled roofing  
Rolled insulation  
Roofing tape

## Machine Specifications

Speed: Up to 20 packages per minute, depending on product  
Electrical: 460 VAC, 3 Ph, 60 Hz, 39 Amp  
Air: 80 psi, 15 SCFM

## Product Specifications

Roll diameter: 3" min to 24" max  
Roll length: 3" min to 48" max

## Film Specifications

Roll Diameter: Up to 14"  
Gauge: Up to 3 mil  
Type: Low density polyethylene (LDPE)  
Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.