



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

nVenia Arpac 708HB Shrink Bundler for the Health / Beauty

At a Glance

- Intermittent-motion, stainless steel construction
- Built for health, beauty, and pharmaceutical industries
- Up to 30 packages per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Right-Angle Intermittent-Motion for Health and Beauty Products

The right-angle intermittent-motion nVenia Arpac 708HB Series shrink bundler is designed specifically for today's pharmaceutical, health and beauty industry. Ultra-compact in design and economical in price, the 708HB bundler is capable of shrink wrapping up to 25 bundles per minute, depending on product specifications. For faster output, this system is available with dual lanes to run up to 50 bundles per minute.

Constructed of stainless steel, the 708HB Series frame is designed for clean operating environments.

Its telescoping tunnel conveyor is designed for fast change of product dead plates and for even transfer of small product from dead plate into the tunnel.

The 708HB Series handles a variety of multi-pack configurations thanks to multi-row collation capabilities and offers a wide range of standard and customized infeeds.

Features

Compact single-frame stainless steel construction

Heavy-duty system for around-the-clock operation

Laser cut and CNC machined components for maximum precision and strength

Right or left-hand mounted infeed and controls

Allen-Bradley programmable logic controller
Arapac operator interface featuring an alphanumeric message display and self-diagnostics
Simple setup and tool-less changeovers for ease of use and minimal downtime
Low maintenance conveyor belts do not require tracking adjustments
Motorized pulleys eliminate chain drives and operate more cleanly, with reduced maintenance cost and less noise
Single stage right-angle infeed conveyor with Intralox belt
Telescoping tunnel conveyor
Bridge plate for small product transfer
Conveyor elevation 35" +2/-0 for easy integration with existing equipment
Powered film unwind
NEMA 12 electrical cabinet and controls
Low film alert warns that a film changeover will soon be necessary
Quick-change seal bar with military-type quick disconnect and replaceable plasma coated inserts
Product hold-down for light products
Top and bottom film racks accommodate four 14" diameter rolls of film
Easy to service air cylinders
Separate pop-up guide and multiple ram stroke programming for multi-row collation
No lubrication required for clean and easy maintenance
Levelers for uneven floors

Example Products

Beauty products
Vials
Cosmetics
Spices
Glass bottles
Spray cans
Boxes
Plastic bottles

Machine Specifications

Speed: Up to 20 packages per minute
Electrical: 208, 230 or 460 VAC, 3 Ph, 60Hz
Air: 80 psi, 8 SCFM

Product Specifications

Width (across machine): .75" to 6"
Length (flow direction): .75" to 11"
Height Range: .5" to 8"

Film Specifications

Roll Diameter: Up to 14"
Gauge: Up to 3 mil
Roll Width: Up to 15"
Type: Polyethylene

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.