**Professional Packaging Systems**
2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

**Contact**
Our Packaging Experts
solutions@propac.com
888-318-0083

# nVenia Arpac HVP Hot Plate Shrink Tunnel

## At a Glance

- Hot plate shrink tunnel with COHRlastic belt for high-speed wrapping
- Pulls seal lines to the bottom of the package
- Ideal for pizzas, stationery, greeting cards and calendars

Buy your shrink bundling film from Pro Pac, and get a discount on this Arpac shrink tunnel!

## Pricing

**Call us at 888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Hot Plate Shrink Tunnel for High-Speed Wrapping

nVenia Arpac HVP Hot Plate Shrink Tunnels produce a complete and uniform shrink in most high-speed wrapping applications by pulling seal lines to the bottom or sides of the package. Typical applications include pizzas, stationery, greeting cards and calendars.

In order to improve the appearance of finished packages, Arpac Hot Plate Tunnels feature a solid heated COHRlastic belt designed to control the location and seal on shrink wrapped products. As the package passes over the heated area of the conveyor, heat causes the seal seams to be pulled underneath or to the sides of the product. Heavy duty variable speed blowers create a high velocity recirculating air system that ensures a contour fit and controls the location of seals by forcing hot air to all points and surfaces of the package.

These tunnels are equipped with thermocouple temperature controls, solid belt conveyors, calrod heating elements and UL listed control panels. Tunnels are available in either single or dual zones and are offered with a powder coat paint or stainless steel finish.

Arpac Hot Plate Shrink Tunnels are manufactured in the USA in accordance with Arpac's Lean Manufacturing Process (AM2) to ensure quality, performance and value.

## Features

Powder coat finish that provides a durable scratch resistant surface and prevents corrosion
Trouble-free user-friendly controls assure optimal operation
Calrod heating elements
Heavy-duty, high quality components and rugged construction provide continuous operation with minimal maintenance

Copyright © 2024 Professional Packaging Systems

Variable speed conveyor ensures uniform shrink and is adjustable to meet production requirements
Thermocouple temperature control provides precise temperature control
Circuit breaker protected components for easy troubleshooting and minimal maintenance
Recirculating heating system consumes less electrical energy by minimizing heat loss

## Machine Options

DC Variable speed blower motors
Casters for machine portability
Stainless steel construction
Tunnel blower
Side smoothing rollers

## Tablet Options

Tablet with Pre-Loaded Documentation Files: operation manual, electrical schematics, BOMs, spare parts list, spares ordering link, stop watch, conversion calculator, and Factory Acceptance reports.
Tablet with Pre-Loaded Documentation Files and Training Module (maintenance, change over, trouble shooting, videos etc.)

## Example Products

Calendars
CDs/DVDs
Food products
Games
Greeting cards
Mailers
Paper products
Pizzas

## Film Types

Polyolefin
Polyethylene
PVC

Copyright © 2024 Professional Packaging Systems

# Specifications of Arpac Hot Plate Shrink Tunnels

| Model | Tunnel Chamber | Machine | Conveyor Drive | Blower Motor | Conveyor Height | Standard Voltages | Element Assembly | Hot Plate | Shipping Weight |
|---|---|---|---|---|---|---|---|---|---|
| HVP122260HP | 22"W x 60"L x 12"H | 31"W x 96"L x 71.25"H | 1/2 HP | 1/2 HP | 36"-38" | 240V/3Ph/60Hz 42A/18kW 480V/3Ph/60Hz 21A/18 kW | 10.5kW | 6kW | 1,000 lbs |
| HVP122290HP | 22"W x 60"L x 12"H | 41"W x 126"L x 71.25"H | 1/2 HP | 1/2 HP | 36"-38" | 240V/3Ph/60Hz 60A 480V/3Ph/60Hz 35A | 21kW | 6kW | 1,250 lbs |
| HVP4/488HP | 40"W x 60"L x 20"H | 61"W x 96"L x 83"H | 1 HP | 1 HP | 36"-38" | 240V/3Ph/60Hz 52A/22kW 480V/3Ph/60Hz 26A/22kW | 18kW | 3kW-6kW | 1,500 lbs |
| HVP4/488 with 737C | 40"W x 60"L x 20"H | 61"W x 96"L x 83"H | 1 HP | 1 HP | 36"-38" | 240V/3Ph/60Hz 42A/18kW 480V/3Ph/60Hz 26A/22kW | 18kW | - | 1,500 lbs |

Please contact Pro Pac or call 888-318-0083 for your shrink bundling equipment.

Copyright © 2024 Professional Packaging Systems