



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Eastey Professional Series Shrink Bundling Tunnels



## At a Glance

- All-welded main frame from 12 gauge steel
- Sealed bearings (not bushings) on drive and idler shafts
- Adjustable digital solid state temperature control
- 78 inch chamber length
- Heavy-duty industrial design and construction for trouble-free service and long life
- Made in the USA

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## High-Performance Bundling Tunnels at Lower Prices

Eastey shrink bundling tunnels are built to provide you with all the quality features found in much higher-priced machines. These heat tunnels are designed and built to give you all the features needed for positive shrinking of polyethylene film.

Eastey bundling tunnels are expertly welded on 12 gauge steel frames and designed to handle the day-to-day demand of most bundling applications. Each tunnel utilizes four-directional variable air flow to provide a positive shrink.

## Models

ETB2416, ETB2420

ETB3616, ETB3620

ETB4816, ETB4820

ETB5616, ETB5620

ETB7016, ETB7020

## Standard Features

Designed to seal polyethylene film  
 All-welded main frame from 12 gauge steel  
 78" chamber length to ensure proper shrinking of film  
 High-temperature belting resists wear  
 Sealed bearings (not bushings) on drive and idler shafts  
 Adjustable digital solid state temperature control for a variety of films  
 Four-directional air flow provides positive shrinking  
 Variable air flow for a variety of products and applications  
 Large ducting creates more air volume inside tunnel  
 Airflow extended to the end of the chamber sides  
 4' product cooling conveyor on exit end  
 Exit cooling fans accelerate shrinking  
 Delayed cool down and over temperature protection  
 Fold down electrical control panel for easy maintenance  
 Heavy-duty casters for transportation within plant  
 Leveling legs provide sturdy base once in place  
 Custom two part epoxy finish resists scratching  
 Available in 220v, single or 3-phase  
 Easy-to-use design requires minimal training, maintenance, and trouble free operation  
 Made in the USA

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.

## Specifications of the Eastey Professional Series Shrink Bundling Tunnels

| Model   | Machine Dimensions |                |                 | Chamber Dimensions |               |                | Conveyor        | Standard Power |      |       | Weight         | Ship Wt.        |
|---------|--------------------|----------------|-----------------|--------------------|---------------|----------------|-----------------|----------------|------|-------|----------------|-----------------|
|         | Width              | Height         | Length          | Width              | Height        | Length         | Length          | Volts          | Amps | Phase |                |                 |
| ETB2416 | 43"<br>(109cm)     | 56"-           | 149"<br>(378cm) | 24"<br>(60cm)      | 16"<br>(40cm) | 78"<br>(198cm) | 147"<br>(373cm) | 480            | 30   | 3     | 1900           | 2000            |
|         |                    | 72"<br>(183cm) |                 |                    |               |                |                 |                |      |       | lbs<br>(861kg) | lbs<br>(908kg)  |
| ETB2420 | 43"<br>(109cm)     | 56"-           | 149"<br>(378cm) | 24"<br>(60cm)      | 20"<br>(50cm) | 78"<br>(198cm) | 147"<br>(373cm) | 480            | 30   | 3     | 1900           | 2000            |
|         |                    | 72"<br>(183cm) |                 |                    |               |                |                 |                |      |       | lbs<br>(861kg) | lbs<br>(908kg)  |
| ETB3616 | 55"<br>(139cm)     | 56"-           | 149"<br>(378cm) | 36"<br>(91cm)      | 16"<br>(40cm) | 78"<br>(198cm) | 147"<br>(373cm) | 480            | 60   | 3     | 2200           | 2300            |
|         |                    | 72"<br>(183cm) |                 |                    |               |                |                 |                |      |       | lbs<br>(997kg) | lbs<br>(1043kg) |

|         |         |                 |         |         |        |         |         |     |             |   |                     |                     |
|---------|---------|-----------------|---------|---------|--------|---------|---------|-----|-------------|---|---------------------|---------------------|
| ETB3620 | 55"     | 56"-<br>72"     | 149"    | 36"     | 20"    | 78"     | 147"    | 480 | 60          | 3 | 2200                | 2300                |
|         | (139cm) | (142-<br>183cm) | (378cm) | (91cm)  | (50cm) | (198cm) | (373cm) |     |             |   | lbs<br>(997<br>kg)  | lbs<br>(1043<br>kg) |
| ETB4816 | 67"     | 56"-<br>72"     | 149"    | 48"     | 16"    | 78"     | 147"    | 480 | 100-<br>120 | 3 | 2600                | 2700                |
|         | (170cm) | (142-<br>183cm) | (378cm) | (121cm) | (40cm) | (198cm) | (373cm) |     |             |   | lbs<br>(1179<br>kg) | lbs<br>(1224<br>kg) |
| ETB4820 | 67"     | 56"-<br>72"     | 149"    | 48"     | 20"    | 78"     | 147"    | 480 | 100-<br>120 | 3 | 2600                | 2700                |
|         | (170cm) | (142-<br>183cm) | (378cm) | (121cm) | (50cm) | (198cm) | (373cm) |     |             |   | lbs<br>(1179<br>kg) | lbs<br>(1224<br>kg) |
| ETB5616 | 75"     | 56"-<br>72"     | 149"    | 56"     | 16"    | 78"     | 147"    | 480 | 100-<br>120 | 3 | 2900                | 3000                |
|         | (190cm) | (142-<br>183cm) | (378cm) | (142cm) | (40cm) | (198cm) | (373cm) |     |             |   | lbs<br>(1315<br>kg) | lbs<br>(1360<br>kg) |
| ETB5620 | 75"     | 56"-<br>72"     | 149"    | 56"     | 20"    | 78"     | 147"    | 480 | 100-<br>120 | 3 | 2900                | 3000                |
|         | (190cm) | (142-<br>183cm) | (378cm) | (142cm) | (50cm) | (198cm) | (373cm) |     |             |   | lbs<br>(1315<br>kg) | lbs<br>(1360<br>kg) |
| ETB7016 | 89"     | 56"-<br>72"     | 149"    | 70"     | 16"    | 78"     | 147"    | 480 | 100-<br>120 | 3 | 3200                | 3300                |
|         | (226cm) | (142-<br>183cm) | (378cm) | (177cm) | (40cm) | (198cm) | (373cm) |     |             |   | lbs<br>(1451<br>kg) | lbs<br>(1496<br>kg) |
| ETB7020 | 89"     | 56"-<br>72"     | 149"    | 70"     | 20"    | 78"     | 147"    | 480 | 100-<br>120 | 3 | 3200                | 3300                |
|         | (226cm) | (142-<br>183cm) | (378cm) | (177cm) | (50cm) | (198cm) | (373cm) |     |             |   | lbs<br>(1451<br>kg) | lbs<br>(1496<br>kg) |