



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal T-4832 Shrink Bundling Tunnel



At a Glance

- 48 inch L x 32 inch W x 12 inch H chamber dimensions
- High-velocity air flow with dual mechanical controls
- Three heat zones

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Large Shrink Bundling Tunnel

The Heat Seal large-capacity T-4832 shrink bundling tunnel has a 12" tunnel opening, with internal dimensions of 48" long x 32" wide.

Features

Tunnel Chamber

- Inside tunnel dimensions: 48"L x 32"W x 12"H
- Digital tunnel temperature control
- High-velocity air flow with dual mechanical controls
- Open coil heating element guaranteed for 10 years
- Three heat zones
- High-temperature limit switch
- Automatic cool down extends heating element life

Conveyor Features

- Quick change 5/8" diameter live/dead rollers with 2" spacing
- Unique pre-shrink feature allows for 25% more bottom shrink
- One quarter horsepower motor with adjustable conveyor speeds up to 70 feet per minute

Other Features

- Heavy gauge adjustable height console with levelers and 3" casters
- Two year warranty

Options

Glass filled nylon (GFN) belt
Stainless steel construction (T4832S)
Stainless steel wire mesh belt conveyor
Non-stick mesh belt conveyor (TMB)
Roller Spacing: 1"
Adjustable product guide rails
Pack cooler fan (for polyethylene)
16" high chamber opening (T4832/16)
Left hand reverse flow
Export crating

Specifications of the Heat Seal T-4832 Shrink Bundling Tunnel

Inside Tunnel Dimensions	48"L x 32"W x 12"H(122L x 81W x 30H cm)
Overall Dimensions	74"L x 41"W x 58"H(189L x 104W x 148H cm)
Wattage	12,900
Weight	860 lbs (391 kg)
Conveyor	Variable speed, quick change live/dead silicone covered rollers with 2" spacing
Conveyor Speed	0 - 35 ft/min (0 - 10.7 m/min)0 - 70 ft/min LDR (0 - 21 m/min LDR)
Power	208-240 Volts, 54 Amps, Three Phase

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.