



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

TexWrap DX-130 Intermittent Motion Shrink Bundler



At a Glance

- Uses top & bottom rolls of film
- Workhorse productivity in a compact footprint
- Up to 25 cycles per minute
- Intermittent-motion wrapper
- Integrated shrink tunnel

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Robust and Compact Shrink Bundling

The TexWrap DX-130 inline intermittent motion shrink bundler is an ideal solution for wrapping trays of product. The DX-130 uses top & bottom rolls of film to cover the product which is then conveyed through a heat tunnel to keep product tightly protected and unitized for transport.

The TexWrap DX-130 shrink bundling system delivers workhorse productivity in a compact footprint designed to fit in most any production line. The standard DX shrink bundling system is rated up to 25 cycles per minute, with an available servo seal bar for applications requiring additional precision.

The TexWrap DX-130 has a host of available options such as side feed film cradles, product hold down, manual splice bar or infeed conveyor.

Features & Benefits

Linear Slide Design Used in both the seal jaw closure and carriage travel assembly mean longer life and less maintenance over time.

Ergonomic Powered Film Cradles Film cradles are ergonomically designed to enable faster film changeovers.

Reliable Throughput Servo controlled seal bar provide increased speed and precision.

Robust Construction Heavy-duty welded, tubular frame construction.

Accessible Shrink Tunnel Design With the removal of 8 screws, operator can pull out the calrod heater bank for maintenance.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.

TexWrap DX-130 Specifications

Minimum Bundle Size	4" Height 6" Width (across machine) 7" Length (direction of flow)
Maximum Bundle Size Both height & width cannot be at max dimension	12" Height 24" Width (across machine) 20" Length (direction of flow)
Controls	Allen Bradley
Speed	Up to 25 cycles per minute Package size and film dependent
Maximum Film Width	30"
Maximum Film Diameter	14"
Film Types	Clear LDPE film 1.5 to 3.0 mil
Construction	Heavy-duty welded tubular steel standard Corrosion resistant construction optional
Orientation	Right or left-hand configuration available

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.