



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Texwrap BVS Vertical Seal Shrink Bundling Equipment



At a Glance

- Multi-packs products that exit upstream equipment in a vertical position
- Eliminates labor and expense of laying product down prior to wrapping
- Automatic orienter positions all product labels in precisely the same direction

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Bundle Products in a Vertical Position

Texwrap BVS vertical shrink bundlers use dual-axis servo technology to wrap products in an upright position. Ideal for multi-packs or variety packs of bottles, cans, jars, and canisters. Use in line with a filler while product is vertical. This vertical seal bundler eliminates labor and expense of laying product down prior to wrapping.

Texwrap BVS Vertical Sealers are ideally suited to multi-packs and variety packs of bottles, cans, jars, or canisters that exit upstream equipment in a vertical position.

To enhance the retail appearance of multi-packs, Texwrap BVS vertical bundlers combine with an optional automatic label positioning system (an orienter) that positions all product labels in precisely the same direction. In applications where a boot is used to hide bar codes, the wrapper can use printed film or a label to hide bar codes and identify the new unit as a multi-pack.

Texwrap BVS vertical seal bundlers produce very secure and attractive packages.

Features & Benefits

Servo Controlled Seal Jaw Servo controlled seal jaws allowing operation at a higher rate and still maintain consistent, precision seals.

Optimized Product Infeed Texwrap library of infeed designs provide a solution to optimize product output.

Standard Auto-Spacing Control Using vertical or horizontal photo eyes to detect leading and trailing edges of product to create consistent spacing between products.

Centerline Justified Easily paired with Texwrap infeed to provide a precise, consistent flow of product into the wrapper.

Precise Product Control Finely tuned product control through the transition zones to maximize seal strength and quality.

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.

TexWrap BVS Specifications

	BVS-914	BVS-1418
Max Bundle Size Both height & width cannot be at max dimension	14" Height 9" Width Infinite Length	18" Height 14" Width Infinite Length
Max Film Width	24" Centerfold 48" Single wound	36" Centerfold 72" Single wound
Conveyor Speed	Up to 140 feet per minute	Up to 140 feet per minute
Typical Footprint	134"L x 73"W	186"L x 111"W
Construction	Heavy-duty welded tubular steel standard. Corrosion resistant construction optional.	
Orientation	Right or left-hand configuration available	

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink bundling equipment.