



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Axon EZ-Wide Low-Speed Shrink Sleeve Applicator



## At a Glance

- Accommodates film layflat widths up to 900 mm (35.4in)
- For containers requiring wide multi-pack, wide twin packs, wide tamper evident bands, or wide shrink sleeve labels
- Single-head and dual-head configurations

Buy your [shrink sleeves](#) from us, and get a discount on this Axon shrink sleeve applicator!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Shrink Sleeving Film Layflat Widths Up to 900 mm (35.4")

Axon's EZ-Wide applicators are the value priced, low to mid-speed models for containers requiring wide multi-pack, wide twin packs, wide tamper evident bands, or wide shrink sleeve labels. These vacuum style shrink sleeve machines use economical stepper motors for consistent, repeatable performance.

The EZ-Wide series includes three shrink sleeving machines that accommodate film layflat widths up to 900 mm (35.4"). These models are ideal for applying multi-pack sleeves, tamper evident neck bands or shrink sleeve labels to large containers or multi-packs.

Axon EZ-Wide shrink sleeve applicators are offered with single-head and dual-head configurations, and are capable of steady-state production speeds from 60 to 90 cpm depending on container size.

## Features & Benefits

**Fully-automatic** - Sleeve application process is fully-automated, recipe driven and a touch screen HMI makes operation simple.

**Large size capable** - Container diameters or multi-pack cross sections up to 22.5" (571 mm).

**Simple to operate, easy to maintain** - Design minimizes use of moving parts which reduces complexity for both operators and maintenance personnel.

**Fast, tool-less size changeovers** - Size changeovers can be completed in five minutes or less.

**Guillotine style cutter** - Simple, durable and dependable two-blade cutting system delivers consistent, clean cuts.

**Long blade life** - Under normal operating conditions EZWide cutting blades can be used for up to one year before replacement is required.

**Modular head design** - Single head applicator can be easily upgraded to a dual heads for increased production speeds.

**Vacuum spreader guide system** - Simple vacuum technology with inexpensive film spreader guides makes change parts inexpensive, and a true bargain.

**Quick changeovers** - Recipe functionality on the touch-screen HMI allow for rapid adjustment of machine settings.

**Cutting system** - Guillotine knife mechanism provides a clean and precise cut for a high-quality finish, it's also simple to maintain.

**Low-cost change parts** - Run all your SKUs on one machine, switching between different size containers won't break your budget.

**Bilingual operation** - English and Spanish standard.

**Multiple perforation options** - Horizontal, T-style, or vertical.

**PMMI certified training** - Operator training provided by a PMMI Certified Technician.

## Applications

The Axon EZ-Wide offers the flexibility to perform multiple shrink applications.

Multi-packs and twin packs

Tamper evident bands

Partial-body sleeves

Full-body sleeves

Full-body over the cap sleeves

## Options

**Static reduction** - Mitigates static build-up.

**Print registration** - Fiber optic sensor reads film registration marks so the PLC can calculate cut lengths to assure sleeve length accuracy.

**Vertical, horizontal & T perforators** - Add perforations to enhance ease of opening.

**Band positioning** - Belt system assures correct placement of tamper bands or partial body sleeves during application process.

**Low film alarm** - Automatically detects low film levels and alerts operator.

**Product spacers** - Precisely separate containers at the infeed to assure smooth production.

**Infeed timing screws** - Required for multi-packs, certain container geometries.

**Spare parts kit** - Recommended start-up parts inventory.

## Specifications

	EZ-400	EZ-650	EZ-900
1 Head Speed	Up to 50 cpm	Up to 40 cpm	Up to 35 cpm
2 Head Speed	Up to 90 cpm	Up to 70 cpm	Up to 60 cpm
Film Layflat Range	200 mm - 400 mm	250 mm - 650 mm	250 mm - 900 mm
Product Diameter or Multi-Pack Cross Section	125 mm - 250 mm	155 mm - 410 mm	155 mm - 571 mm
Applied Film Materials	PVC, PETG, OPS, PLA		
Film Thickness	60 - 70 microns (2.3 - 3.0 mil)		70 - 100 microns (3.0 - 4.0 mil)
Controls	Siemens PLC & HMI standard, Allen Bradley optional		
Power	220V Single ph		
Air	80 psi, 5-10 cfm		

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink sleeve equipment.