



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Axon EZ-150SL Low-Speed Shrink Sleeve Applicator



At a Glance

- Compact mandrel style applicator offering speeds up to 150 cpm
- Widely used in the craft beer industry
- Robust stainless steel frame

Buy your [shrink sleeves](#) from us, and get a discount on this Axon shrink sleeve applicator!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Dependable Shrink Sleeving Speeds Up to 150 CPM

Axon's EZ-150SL is a value priced, small footprint, low-speed shrink sleeve applicator designed to run up to 150 containers per minute. The EZ-150SL is a mandrel style machine developed for ready-to-drink beverage cans and it is widely used in the craft beer industry.

EZ-150SL sleeve applicators use servo motion control to deliver consistent, repeatable performance. Container changeovers are tool-less and require less than ten minutes depending on product sizes and shapes.

These shrink sleeve applicators feature robust stainless steel frames that are designed with beverage plant operating conditions in mind.

Features & Benefits

Size range flexibility - Container or multipack diameters range from 1.2" (30 mm) to 4.9" (125 mm). Larger sizes are compatible with EZ-Wide or Aurora Wide applicators.

Fast, tool-less size changeovers - Size changeovers can be completed in less than ten minutes depending on container sizes and shapes.

Servo motion control - High performance motion control delivers fast and accurate film feeding, film registration, and cutting.

Intuitive, industry standard PackML programming & HMI user interfaces - Consistent terminology, consistent screen displays and standardized program structures enhance ease of operation and maintenance.

Electronic height adjustment - Push-button system eliminates manual hand-crank height adjustments.

Sealed-for-life bearings - Lubrication free bearings and servo motion control make the EZ-150SL a lubrication free machine.

Applications

The Axon EZ-150SL offers the flexibility to perform multiple shrink applications.

Tamper evident bands

Partial-body sleeves

Full-body sleeves

Multi-packs

Options

Dynamic speed control - Enables the machine to automatically increase or decrease speeds based on line conditions.

Print registration - Fiber optic sensor reads film registration marks so the PLC can calculate cut lengths to assure sleeve length accuracy.

Vertical perforator - Adds vertical perforations for easy opening.

Inspection rejection system - Detects high label, low label, and no label.

Spare parts kit - Recommended start-up spare parts inventory.

Specifications

Speed	Up to 150 cpm
Film Layflat Range	50 mm - 200 mm (2.0" - 7.8")
Applied Film Materials	PVC, PETG, OPS, PLA
Film Thickness	40 - 70 microns (1.5 - 3.0 mil)
Product Diameter	30 mm - 125 mm (1.18" - 4.92")
Controls	Siemens standard, Allen Bradley optional
Machine Frame	Stainless steel
Power	220V Single or 3ph

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink sleeve equipment.