



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Axon SLX High-Speed Shrink Sleeve Applicator



At a Glance

- Steady-state production speeds up to 800 CPM
- Servo motion control delivers consistent, repeatable performance
- Tool-less changeovers in less than ten minutes

Buy your [shrink sleeves](#) from us, and get a discount on this Axon shrink sleeve applicator!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Dependable Shrink Sleeving Speeds Up to 800 CPM

Axon high-speed, high performance SLX Series shrink sleeve label applicators provide dependable, steady-state production speeds up to 800 containers per minute.

SLX sleeve applicators are mandrel style machines that use servo motion control to deliver consistent, repeatable performance. Container changeovers are tool-less and require less than ten minutes depending on product sizes and shapes.

Dual-segment feedscrews with independent servo control of each segment provide smooth and flexible container handling.

When equipped with the optional thin gauge film handling system SLX applicators are capable of running the thinnest films available in the industry with no reduction in speed or efficiency.

Features & Benefits

Size range flexibility - Container diameters range from 1.2" (30 mm) to 4.9" (125 mm).

Fast, tool-less size changeovers - Size changeovers can be completed in less than ten minutes depending on container sizes and shapes.

Servo motion control - Dedicated servo drives for the feedscrew, film feed system, and cutting assembly deliver fast, accurate film feeding, film registration and cutting.

Intuitive, industry standard PackML programming & HMI user interfaces - Consistent terminology, consistent screen displays and standardized program structures enhance ease of operation and maintenance.

Auto-reversing cutter assembly & dual edge blades - Dual edge cutting blades with a programmed auto-reversing cutting system extends blade life and reduces frequency of blade replacement.

Electronic height adjustment - Simple to use push-button system eliminates manual hand-crank height adjustments.

Digital recipe parameter control - Assures that machine will not start production, or continue production, if one or more of the 4 key recipe parameters is out of specification. This system is standard on the SLX 800 and improves both operating efficiencies and product quality.

Zero tension film feed - Precisely controlled film feed loop with ultrasonic sensors eliminates dancer arms and unneeded tension on the film web during production.

Automatic speed control - Automatically increase or decrease sleeving rate to match changing line speed without operator input for "set it and forget it" product run.

Powered by Rockwell - Widely used Allen-Bradley controls are standard.

Recipe functionality - Change machine settings with the push of a button for quick changeovers.

Ethernet - Ethernet communications for rapid business systems interface and remote monitoring.

No lubrication required - Sealed for life bearings simplifies maintenance with no lubrication required.

Multiple perforation options - Horizontal, T-style, or vertical.

Left or right-hand orientation - Run either left or right handed operations to fit your packaging line.

Electric height adjustment - No hand cranks, simple push button control.

Bilingual operation - English and Spanish HMI for your diverse workforce.

PMMI certified training - Operator training provided by a PMMI Certified Technician.

Applications

The Axon SLX offers the flexibility to perform multiple shrink applications.

Tamper evident bands

Partial body sleeves

Full body sleeves

Full body over-the-cap sleeves

Options

Thin gauge film handling system - Enables the machine to run the thinnest films available in the industry.

Dynamic speed control - Enables the machine to automatically increase or decrease speeds based on line conditions.

Print registration - Fiber optic sensor reads film registration marks so the PLC can calculate cut lengths to assure sleeve length accuracy.

Vertical, horizontal & T perforators - Add perforations to enhance ease of opening.

Swing arm HMI - Provides flexible access to machine controls.

Inspection rejection system - Detects high label, low label, no label, and incorrect bar codes; includes secondary conveyor rejection system at discharge.

Spare parts kit - Recommended start-up parts inventory.

Specifications

	SLX-600	SLX-800
Speed	Up to 600 cpm	Up to 800 cpm
Film Layflat Range	50 mm - 200 mm (2.0" - 7.8")	
Product Diameter or Multi-Pack Cross Section	30 mm - 125 mm (1.2" - 4.9")	
Applied Film Materials	PVC, PETG, OPS, PLA	
Machine Frame	Extruded aluminum	304 stainless steel
Language Support	English and Spanish with one-touch toggle control	
Lubrication System	Sealed-for-life bearings and servo motion control	
Film Thickness	40 - 70 microns (1.5 - 3.0 mil) standard, thin-gauge film tooling optional	
Film Unwind	Dual-reel film unwind with festoon film accumulation + manual splice on the fly	Dual-reel film unwind + auto-splicer
Digital Recipe Parameter Control	Optional	Standard
Controls	Allen Bradley standard	
HMI	10" Allen Bradley PanelView standard	
Servos	Allen Bradley standard	
Electrical Enclosure	NEMA 12 standard, NEMA 4X optional	
Power	480V 3 ph	

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink sleeve equipment.