



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Heat Seal SB-2615 Shrink Banding Heat Tunnel



At a Glance

- 26 inch L x 15 inch W x 8 inch H chamber dimensions
- Single heat zone
- U.L. listed control panel

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Single Heat Zone Tamper Band Shrink Tunnel

Heat Seal SB-2615 Shrink Banding Heat Tunnels are designed for mid-volume application of tamper-evident shrink bands.

Features

Tunnel Chamber

Inside Tunnel Dimensions: 26"L x 15"W x 8"H

U.L. listed control panel

Digital tunnel temperature control

Adjustable opening stainless steel doors with attached product guide rails

High-velocity air flow with adjustable side air manifolds

Open coil heating element guaranteed for 10 years

Single heat zone

High-temperature limit switch

Automatic cool down extends heating element life

Conveyor Features

Intralox high-temperature variable speed conveyor

One-quarter horsepower motor with adjustable conveyor speeds of up to 35 feet per minute

Other Features

Heavy gauge adjustable height console with levelers and 3" casters
Two year warranty

Options

Stainless steel construction
12" high chamber opening
Shrink band hold down kit
Left hand reverse flow

Specifications

Inside Tunnel Dimensions: 26"L x 15"W x 8"H (66L x 38W x 20H cm)
Conveyor Speed: 0 - 35 ft/min (10.7 m/min)
Conveyor: Variable speed, Intralox belt
Overall Dimensions: 41"L x 24"W x 52"H (104L x 61W x 132H cm)
Weight: 420 lbs (191 kg)
Power Requirements: 208~220 Volts, 25 Amps, Single Phase
Wattage: 5,500 Watts

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.