



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Heat Seal SB-3422 Shrink Banding Heat Tunnel



## At a Glance

- 34 inch L x 22 inch W x 10 inch H chamber dimensions
- Dual heat zones
- U.L. listed control panel

Buy your [shrink film](#) from us, and get a discount on this Heat Seal shrink tunnel!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Dual Heat Zone Tamper Band Shrink Tunnel

Heat Seal SB-3422 Shrink Banding Heat Tunnels are designed for mid-volume application of tamper-evident shrink bands.

## Features

### Tunnel Chamber

Inside Tunnel Dimensions: 34"L x 22"W x 10"H

U.L. listed control panel

Digital tunnel temperature control

Adjustable opening stainless steel doors with attached product guide rails

High-velocity air flow with adjustable side air manifolds

Open coil heating element guaranteed for 10 years

Dual heat zones

High-temperature limit switch

Automatic cool down extends heating element life

### Conveyor Features

Intralox high-temperature variable speed conveyor

One-quarter horsepower motor with adjustable conveyor speeds of up to 35 feet per minute

## Other Features

Heavy gauge adjustable height console with levelers and 3" casters

Two year warranty

## Options

Stainless steel construction  
14" high chamber opening  
Shrink band hold down kit  
Left hand reverse flow

## Specifications

Inside Tunnel Dimensions: 34"L x 22"W x 10"H (86L x 56W x 25H cm)  
Conveyor Speed: 0 - 35 ft/min (10.7 m/min)  
Conveyor: Variable speed, Intralox belt  
Overall Dimensions: 60"L x 31"W x 57"H (153L x 79W x 145H cm)  
Weight: 560 lbs (255 kg)  
Power Requirements: 208~220 Volts, 25 Amps, Single Phase  
Wattage: 2,200 Watts

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.