



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Tripack HSA-405 High-Speed Shrink Sleeve Applicator



At a Glance

- Highest level of operational efficiency and precise sleeve placement
- Built for handling high-speed applications
- Easy-to-operate touch screens
- Mandrel-based film delivery
- Made in the USA

Buy your [shrink sleeves](#) from us, and get a discount on this Tripack shrink sleeve applicator!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Rugged High-Speed Shrink Sleeve Applicator

Tripack HSA-405 shrink label applicators are built for handling high-speed applications, extensive line integration requirements, and heavy production schedules. These applicators are built to last, with rugged stainless steel and aluminum construction, with servo-motion film handling.

Tripack's mandrel-based delivery ensures the highest level of operational efficiency and precise sleeve placement.

Easy-to-operate touch-screens are powered by Allen-Bradley control systems and servo-motion.

Features of the HSA-410T

Eight-point mandrel/bullet design film delivery system with pre-form lower options based on container shape and size. Pre-calibrated clutch wheels for PERFECT mandrel placement and pressure tension.

Allen Bradley touchscreen HMI with recipe-driven sizes for change-over convenience.

Stainless-steel frame locks into place with new or existing conveyor.

Stack light with multiple warning lights and audible alarm.

Powered film assist assembly with ZERO tension film web design.

Allen Bradley servo-driven, high-speed film delivery and multi-blade knife assembly.

Quick-change toolless knife assembly.

Film loading/unwind station for 5" or 10" Core / 19" Film OD.

Cantilever style head capable of running over existing conveyors with fully guarded framing.

Stainless-steel frame with caster wheels and adjustable feet.

Custom film mandrel.

Print registration.
Static reducing ionizer system.

Options

Vertical, horizontal, and T perforation
Wash down design
CompactLogix PLC (HSA model)
Inspection / reject system

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink sleeve equipment.

Specifications of Tripack HSA/MSA Shrink Sleeve Applicators

Model	Product Diameter	Layflat Range (mm)	Cut Length (mm)	Max Speed
MSA-180	1" - 3.75"	40 - 160	30 - 250	200 ppm
HSA/MSA-245	1" - 6"	40 - 245	30 - 250	300 ppm
HSA/MSA-405	1" - 10"	40 - 400	30 - 250	400 ppm