



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Tripack TE-150 Tamper Band Applicator



At a Glance

- Excellent for entry-level packaging needs and light production schedules
- Minimal floor space with cantilever design
- Easy-to-operate touch screens
- State-of-the-art mandrel style film application technology
- Made in the USA

Buy your [shrink sleeves](#) from us, and get a discount on this Tripack shrink sleeve applicator!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Rugged Tamper Band Applicator for Light Production

Tripack TE-150 tamper band applicators are engineered to meet your entry-level packaging needs and light production schedules.

TE-150 applicators take up minimal floor space with their cantilever design. This design allows them to be quickly and easily integrated into your existing packaging line.

Tripack TE-150 tamper band applicators feature state-of-the-art mandrel style film application technology. This gives you maximum production efficiency as well as precision full-body shrink sleeve and tamper-evident neck band application at speeds up to 120 ppm.

All Tripack machines are built with aluminum and stainless steel construction for added durability. They come with caster wheels and leveling feet for mobility and ease of adjustment. TE-150 applicators feature HMI touch-screens and PLC controls for easy, user-friendly operation.

Features of TE-150

Film loading / unwind station for 5" core / 15.5" film OD.

Guillotine knife assembly.

Extruded aluminum frame locks into place with new or existing conveyor.

Caster wheels and adjustable feet.

Stack light with multiple warning lights and audible e-stop.

Mandrel / butterfly film delivery system.

Touchscreen HMI with recipe driven sizes for change over convenience.

Cantilever style head capable of running over existing conveyor lines with adjustable head height

feature.
Print Registration.
Static reducing ionizer system.
3 year warranty.

Options

Vertical perforating

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink sleeve equipment.

Specifications of Tripack TE-150 Tamper Band Applicators

Model	Product Diameter	Layflat Range (mm)	Cut Length (mm)	Max Speed
TE-150	1" - 3.75"	40 - 170	25 - 50	120 ppm