



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Tripack TE-150 Tamper Evident Band Applicator



## At a Glance

- Excellent for entry-level packaging needs and light production schedules
- Applies tamper bands up to 120 ppm
- Minimal floor space with cantilever design
- State-of-the-art mandrel style film application technology
- Made in the USA

Buy your [shrink sleeves](#) from us, and get a discount on this Tripack shrink sleeve applicator!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Rugged Tamper Band Applicator for Light Production

The Tripack TE-150 tamper evident band applicator is an ideal for low to moderate speed tamper evident banding. The TE-150 band applicator's compact design and economical price provides a good entry point for companies looking to automate their packaging line.

The TE-150 efficient mandrel style tamper evident band applicator is capable of running tamper evident bands up to 120 products per minute.

The Tripack TE-150 tamper band applicator's plug and play design takes up minimal floor space and can be integrated into production lines quickly and easily.

This tamper band applicator features a single unwind station with tension control and film registration providing a consistent and accurate cut. Additionally, the cutting unit has a quick-change design to save time changing the blade.

A touchscreen operator panel and stack light make setup and operation fast and simple.

Like all Tripack applicators, the TE-150 has full complement of options, including customized product handling solutions, film accumulation devices, and shrink tunnels.

## Benefits

Reliable and consistent performance  
Easy to install, use and maintain

Simple design allows for quick film change and maximum uptime  
Fully enclosed with interlocked guarding for safe operation  
Mobile frame with casters and adjustable feet  
– Easy to move in and out of production line

## Features of TE-150

Film loading/unwind station for 5" core / 15" film OD  
Mandrel/butterfly film delivery system  
Guillotine knife assembly  
Extruded aluminum frame with caster wheels and adjustable feet  
– Cantilever style design capable of running over existing conveyors  
– Adjustable height feature  
– Locks into place with new or existing conveyor  
Touch screen HMI  
Stack light with multiple warning lights and audible alarm

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink sleeve equipment.

## Specifications of Tripack LSA-160 Shrink Sleeve Applicator

Standard Power	240 Volt, 1 Phase, 15 Amp
Air	5 cfm @ 80 psi
Product Range	1" – 3.75" Diameter
Lay Flat Range	40mm – 150mm
Cut Length Range	20mm – 50mm
Max Speed	120 ppm
Max Film Roll OD	15"
Film Core ID Sizes	5" or 10"
Film Gauge Tolerance	35-70 microns (1.38-2.75 mil)
Lay Flat Tolerance	-0mm / +1mm
Coefficient of Friction	≤ 0.25
Material Types	PET, PETG, OPS, PLA, PVC
Dimensions	52"L x 45"W x 109"H

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink sleeve equipment.