



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Arpac AL Continuous Motion Automatic L-Sealers

## At a Glance

- Up to 40 packages per minute
- Motion control platform with Allen-Bradley MicroLogix PLC and color touch screen
- Direct drive motors eliminate chains, sprockets, tensioners
- Multiple frame and cross seal sizes
- Heavy duty welded frame, double powder coat and stainless steel finish

Buy your [shrink film](#) from Pro Pac, and get a discount on this Arpac shrink wrapper!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



## Fast, User-Friendly, Reliable Automatic L Sealer

The Arpac AL Continuous Motion Automatic L-Sealers are available with a number of plug and play infeeds to fit your present and future needs. Its motion control platform consists of an Allen-Bradley MicroLogix PLC and a Color Touch Screen. Three 1 HP Direct Drive Vector motors drive the side seal, traveling belt and infeed conveyors.

The package activated AutoLength end seal system provides automatic bag-length control or random-length package sealing. The programmable orbit along with electronic bunching produces strong, quality seals with all commercial shrink films.

This platform offers high speed operation, repeatability, low maintenance, reliability and extraordinary flexibility.

## Quality and Workmanship

State of the art controls, heavy duty welded frame, double powder coat and stainless steel finish, oversized drives, cross seal bars with multi-zone heater design and attention to detail by skilled craftsman.

## Versatility

Multiple frame and cross seal sizes, wide range of plug and play infeed choices and a large selection of options and accessories, allows customers to build the machine that fits their needs. The side and cross

seal will run polyolefin, polyethylene and PVC films.

## Low Maintenance

Direct drive motors eliminate chains, sprockets, tensioners and the need for lubrication or any maintenance in those areas. Self-cleaning side seal element only touches the film, it does not use any back up wheels, rubber rollers or separate cutting devices that require maintenance or replacement. Non-stick ceramic Teflon coated cross seal bars resist build up.

## User Friendly

Color touch screen on swivel allows two sided operation, can store up to 100 package recipes, includes self diagnostics and a troubleshooting guide. Tool-less changeover enables quick product change. Large gull wing doors allow easy access to major machine assemblies for periodic cleaning and inspection.

## Efficiency

Efficient film usage is due to the direct film delivery path and side seal design. The dancer bar controlled selvage winder controls film trim tension so that minimal waste is produced. Digitally controlled bag length produces consistent packages for optimum display of your product. Step by step programming and large library recipe storage yields maximum up time during product changeover.

## Machine Specifications

Film Speed: 100 feet per minute

Package Rate: Up to 75 per minute

Electrical Power Requirements: 208/240VAC, 30A, 3Ph, 60HZ

Compressed Air Requirements: 4CFM @ 80PSI

## Film Specifications

Roll Diameter: Up to 11.5"

Roll Width: Up to 30"

Type: Polyethylene, Polyolefin, PVC

Clear or randomly printed film

Center fold

## Specifications of AL Automatic L-Sealers

Model	Max Package	Seal	Matching Tunnel	Max Film Width
AL18	Infinite"L x 18"W x 8"H	20"W x 8.5"L	XT18	25" CF, 50" flat
AL24	Infinite"L x 24"W x 12"H	26"W x 12.5"L	XT30	31" CF, 62" flat
AL30	Infinite"L x 30"W x 12"H	33"W x 12.5"L	XT30	38" CF, 76" flat

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.