



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey Automatic L-Sealers



At a Glance

- Power film unwind provides proper tension of film
- Hot knife seal system ensures a clean, positive, and even seal every time
- Film take-up scrap winder automatically wraps up scrap film from the sealer
- Simple, easy-to-use control panel lets operators adjust for each specific application
- All-welded main frame from quarter-inch cold rolled steel
- Heavy-duty industrial design and construction for trouble-free service and long life
- Made in the USA

Buy your [shrink film](#) from us, and get a discount on this Eastey L sealer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Automatic L-Sealers for Large Heavy Products

Eastey has been a leader in the shrink packaging industry for over 25 years. Eastey Automatic L-Sealers offer the durability and functionality required to efficiently handle a variety of shrink applications.

Eastey Automatic L-Sealers provide top of the line features and the most robust L-Sealer design on the market today. Expertly welded from 0.25" cold rolled steel, Eastey L-Sealers reliably perform in the most demanding real-world shrink wrap production requirements.

Eastey Automatic L-Sealers are designed specifically for large or heavy products that need to be fully enclosed. The efficient automatic self centering seal system allows users to automatically seal product that is placed on the infeed conveyor for a consistent seal every time. These industrial-strength machines are built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin, polyethylene, and PVC.

Models

EA3050TK, EA3070TK, EA30100TK

EA4050TK, EA4070TK, EA40100TK

EA5050TK, EA5070TK, EA50100TK

Standard Features

Designed to seal most polyolefin, polyethylene, and PVC shrink films
All-welded main frame from 0.25" cold rolled steel
Soft start infeed and outfeed conveyors to reduce shifting of products
Variable speed infeed and outfeed conveyors
Side adjustable film rack for perfect alignment
Seal head casting equipped with pneumatic air cylinder for automatic sealing
Hot knife seal available with mushroom (standard), pancake, arrow, or poly inserts
Consistent pressure across seal bar
Automatic cycle timing with adjustable dwell time
PLC controlled with product indexing
Film tracking wheels keep film in place
Power film unwind ensures proper tension of film
Multiple pin perforators provide air evacuation
Power film take-up scrap winder included
Custom two-part epoxy finish resists scratching
Heavy-duty casters for transportation within plant
Easy-to-use design requires minimal training and maintenance
Side seal size 30", 40", or 50"; front seal size 50", 70", or 100"
Maximum film width up to 60"
Maximum film roll OD up to 12"
60 PSI
Available in 220v, or 480v
Made in the USA

Please [contact Pro Pac](#) or call 888-318-0083 for your shrink equipment.

Specifications of the Eastey Automatic L-Sealer

Model	Seal Dimensions		Machines Dimensions			Standard Power			Weight	Ship Wt.
	Front	Side	Width	Height	Length	Volts	Amps	Phase		
EA3050TK	50" (127cm)	30" (76cm)	86" (218cm)	74" (187cm)	163" (414cm)	220	30/35	1	4600 lbs (2086 kg)	4800 lbs (2177 kg)
EA3070TK	70" (178cm)	30" (76cm)	86" (218cm)	74" (187cm)	183" (464cm)	220	30/35	1	5000 lbs (2267 kg)	5200 lbs (2358 kg)
EA30100TK	100" (254cm)	30" (76cm)	86" (218cm)	74" (187cm)	213" (541cm)	220	30/35	1	5300 lbs (2404 kg)	5500 lbs (2494 kg)
EA4050TK	50" (127cm)	40" (102cm)	86" (218cm)	74" (187cm)	163" (414cm)	220	30/35	1	5100 lbs (2313 kg)	5300 lbs (2404 kg)
EA4070TK	70" (178cm)	40" (102cm)	86" (218cm)	74" (187cm)	183" (464cm)	220	30/35	1	5500 lbs (2494 kg)	5700 lbs (2585 kg)
EA40100TK	100" (254cm)	40" (102cm)	86" (218cm)	74" (187cm)	213" (541cm)	220	30/35	1	5800 lbs (2630 kg)	6000 lbs (2721 kg)
EM5050TK	50" (127cm)	50" (127cm)	96" (243cm)	74" (187cm)	163" (414cm)	220	30/35	1	5600 lbs (2540 kg)	5800 lbs (2630 kg)
EM5070TK	70" (178cm)	50" (127cm)	96" (243cm)	74" (187cm)	183" (464cm)	220	30/35	1	6000 lbs (2721 kg)	6200 lbs (2812 kg)
EM50100TK	100" (254cm)	50" (127cm)	96" (243cm)	74" (187cm)	213" (541cm)	220	30/35	1	6300 lbs (2857 kg)	6500 lbs (2948 kg)